

Package ‘confoundvis’

October 18, 2026

Type Package

Title A Common Interface for Visualizing and Reporting Sensitivity
Analyses for Unmeasured Confounding

Version 0.3.0

Description A common interface to established sensitivity analyses for unmeasured confounding in observational studies. Results of impact threshold and robustness of inference to replacement analysis (Frank, 2000, <[doi:10.1177/0049124100029002001](https://doi.org/10.1177/0049124100029002001)>; Frank et al., 2013, <[doi:10.3102/0162373713493129](https://doi.org/10.3102/0162373713493129)>), partial R-squared omitted-variable bias analysis (Cinelli and Hazlett, 2020, <[doi:10.1111/rssb.12348](https://doi.org/10.1111/rssb.12348)>), E-values (VanderWeele and Ding, 2017, <[doi:10.7326/M16-2607](https://doi.org/10.7326/M16-2607)>), and Rosenbaum bounds for matched pairs (Rosenbaum, 2002, <[doi:10.1007/978-1-4757-3692-2](https://doi.org/10.1007/978-1-4757-3692-2)>) are stored in one object that keeps each framework's own parameter. Robustness curves, summary tables, and plain-language reports are available for every framework; two-parameter surfaces, the exact correlation contour, and observed-covariate benchmarks are provided where the corresponding framework defines them. Results can be computed from fitted models or matched-pair differences, or converted from the 'sensemakr', 'konfound', and 'EValue' packages, and agree with those packages.

License GPL-3

Encoding UTF-8

Language en-US

Depends R (>= 4.1.0)

Imports ggplot2 (>= 3.4.0), rlang, graphics, grDevices, stats

Suggests testthat (>= 3.0.0), knitr, rmarkdown, sensemakr, konfound, EValue, DOS2, sensitivity2x2xk, sensitivitymv, ggrepel

Config/testthat/edition 3

VignetteBuilder knitr

URL <https://github.com/subirhait/confoundvis>

BugReports <https://github.com/subirhait/confoundvis/issues>

NeedsCompilation no
Config/roxygen2/version 8.0.0
Author Subir Hait [aut, cre] (ORCID: <<https://orcid.org/0009-0004-9871-9677>>)
Maintainer Subir Hait <haitsubi@msu.edu>
Repository CRAN
Date/Publication 2026-10-17 22:40:29 UTC

Contents

as.data.frame.confoundsens	2
as_confoundsens	3
covariate_impacts	4
from_value	6
from_konfound	7
from_sensemakr	8
itcv_lm	9
new_confoundsens	10
plot_robustness_curve	11
plot_sensitivity_contour	12
plot_sensitivity_love	14
plot_sensitivity_surface	15
print.confoundsens	16
rir_lm	16
robustness_points	18
sens_path_lm	18
sens_path_pairs	20
sens_report	21
sens_surface	22
sens_table	24
summary.confoundsens	25
Index	26

as.data.frame.confoundsens	
	<i>Coerce a confoundsens object to a data frame</i>

Description

Coerce a confoundsens object to a data frame

Usage

```
## S3 method for class 'confoundsens'  
as.data.frame(x, ...)
```

Arguments

`x` A 'confoundsens' object.
`...` Unused; included for S3 method consistency.

Value

A data.frame with columns 'lambda' and 'theta', plus optional columns 'level', 'se', and 't' when present in 'x'.

Examples

```
x <- new_confoundsens(
  lambda = seq(0, 0.2, length.out = 5),
  theta  = seq(1, 0.8, length.out = 5),
  se      = rep(0.05, 5)
)
as.data.frame(x)
```

as_confoundsens	<i>Convert a data frame to a confoundsens object</i>
-----------------	--

Description

Converts a data frame containing sensitivity analysis results into a 'confoundsens' object suitable for use with 'confoundvis' plotting functions.

Usage

```
as_confoundsens(data, ...)

## Default S3 method:
as_confoundsens(data, ...)

## S3 method for class 'lm'
as_confoundsens(data, ...)

## S3 method for class 'sensemakr'
as_confoundsens(data, ...)

## S3 method for class 'data.frame'
as_confoundsens(
  data,
  lambda = "lambda",
  theta  = "theta",
  level  = NULL,
  se     = NULL,
  t      = NULL,
  ...
)
```

Arguments

<code>data</code>	A <code>data.frame</code> containing sensitivity analysis results, a fitted ‘lm’ model, or a ‘sensemakr’ object.
<code>...</code>	Passed to methods. For ‘lm’ objects, ‘treatment’ (required), ‘lambda’, and ‘ratio’; for ‘sensemakr’ objects, ‘lambda’ and ‘ratio’.
<code>lambda</code>	Character string; name of the column containing lambda values. Default “lambda”.
<code>theta</code>	Character string; name of the column containing theta values. Default “theta”.
<code>level</code>	Optional character string; name of the column containing subgroup (stratum) labels (e.g., “female” / “male”).
<code>se</code>	Optional character string; name of the column containing standard errors for ‘theta’.
<code>t</code>	Optional character string; name of the column containing test statistics.

Details

‘as_confoundsens()’ is generic. The data-frame method (the 0.1.0 behaviour) maps columns to fields. Methods for fitted ‘lm’ models and ‘sensemakr’ objects compute the partial R^2 path via [sens_path_lm()] and [from_sensemakr()]; see also [from_konfound()] and [from_evalue()].

Value

A ‘confoundsens’ object.

Examples

```
df <- data.frame(
  lambda = seq(0, 0.2, length.out = 10),
  theta = seq(1, 0.5, length.out = 10),
  se = rep(0.1, 10),
  level = rep(c("female", "male"), length.out = 10)
)
x <- as_confoundsens(df)
x

# Directly from a fitted model
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
as_confoundsens(fit, treatment = "am")
```

covariate_impacts

Benchmark observed covariates against a sensitivity threshold

Description

For each covariate term in a fitted linear model (other than the treatment and the intercept), computes how strongly it is related to the treatment and to the outcome. These are the observed benchmarks that analysts compare with a sensitivity threshold ("would an omitted variable as strong as this covariate overturn the result?").

Usage

```
covariate_impacts(
  model,
  treatment,
  metric = c("itcv", "partial_r2"),
  alpha = 0.05
)
```

Arguments

model	A fitted ‘lm’ object.
treatment	Character string naming the treatment coefficient.
metric	Which metric populates the ‘impact’ column used by [plot_sensitivity_love()]: “itcv” (default) or “partial_r2”.
alpha	Two-sided significance level used for the ITCV threshold.

Details

Two metrics are returned:

‘impact’ (ITCV metric) $r_{DZ|W} \times r_{YZ|W}$, the product of partial correlations of the covariate with the treatment and with the outcome, each conditioning on the remaining covariates W (as in Frank, 2000). Compared with the ITCV. Only positive values (same sign as the estimate) push the estimate toward zero; the returned ‘impact’ is signed so that positive means “reduces the estimate”. Defined only for single-column terms.

‘bias_index’ (partial R^2 metric) $\sqrt{R_{Y \sim Z|D,W}^2 R_{D \sim Z|W}^2 / (1 - R_{D \sim Z|W}^2)}$. An omitted confounder with this pair of partial R^2 values would move the estimate by ‘bias_index’ $\times se\sqrt{df}$, so it would bring the point estimate to zero when ‘bias_index’ exceeds $|t|/\sqrt{df}$. Defined for multi-column terms (factors) as well.

The returned data frame carries an attribute ‘threshold’ for the selected ‘metric’, so it can be passed straight to [plot_sensitivity_love()]. Its ‘r_yu’, ‘r_du’, and ‘label’ columns can be passed as ‘benchmarks’ to [plot_sensitivity_contour()].

Covariate benchmarks describe *observed* variables. Whether an unobserved confounder could be as strong as a given covariate is a substantive judgment that no benchmark can settle.

Value

A data frame with one row per covariate term and columns ‘covariate’, ‘term_df’, ‘r_du’, ‘r_yu’, ‘itcv_impact’, ‘r_du_zero’, ‘r_yu_zero’, ‘impact_zero’, ‘r2dz.x’, ‘r2yz.dx’, ‘bias_index’, ‘itcv_ratio’, ‘impact’, and ‘label’, and attributes ‘threshold’, ‘metric’, ‘itcv’, and ‘f_threshold’. ‘r_du_zero’ and ‘r_yu_zero’ are the zero-order (unadjusted) correlations of a single-column term with treatment and outcome, ‘impact_zero’ their signed product, and ‘itcv_ratio’ the unconditional ITCV divided by ‘impact_zero’ (Frank et al., 2025, eq. 10), reported for terms whose impact acts against the estimate. A ratio above 1 means an omitted variable would need a larger impact than that covariate.

References

Frank, K. A., Saw, G. K., Lin, Q., Xu, R., Rosenberg, J. M., Maroulis, S. J., & Staudt Willet, K. B. (2025). *A practical guide to impact threshold of a confounding variable (ITCV) and robustness of inference to replacement (RIR)* (Version 2). doi:10.31234/osf.io/pdgbz_v2

Examples

```
fit <- lm(mpg ~ am + wt + hp + qsec, data = mtcars)
imp <- covariate_impacts(fit, "am")
imp
plot_sensitivity_love(imp)
```

from_evalue

Convert an E-value result to a confoundsens path

Description

Builds a bias-adjusted risk-ratio path from an ‘evalue’ object (as returned by ‘EValue::evaluates.RR()’, ‘evaluates.OR()’, ‘evaluates.HR()’, ‘evaluates.OLS()’, and related functions). Confounder strength λ is the common risk ratio relating the confounder to both treatment and outcome; the corresponding bias factor is $B = \lambda^2 / (2\lambda - 1)$ (VanderWeele and Ding, 2017). The path is on the log risk-ratio scale, so it crosses the null (0) exactly at the E-value.

Usage

```
from_evalue(x, lambda = seq(1, 5, by = 0.02))
```

Arguments

x	An object of class “evalue”.
lambda	Numeric vector of confounder risk ratios (≥ 1).

Value

A ‘confoundsens’ object with ‘theta’ = log of the bias-adjusted point risk ratio and, when the confidence interval is available, ‘se’ on the log scale.

References

VanderWeele, T. J., & Ding, P. (2017). Sensitivity analysis in observational research: Introducing the E-value. *Annals of Internal Medicine*, 167(4), 268–274. doi:10.7326/M162607

Examples

```
e <- EValue::evaluates.RR(est = 1.8, lo = 1.3, hi = 2.5)
path <- from_evalue(e)
robustness_points(path)
```

from_konfound

*Convert konfound output to a confoundsens path***Description**

Builds a path from the output of ‘konfound::konfound()’ or ‘konfound::pkonfound()’ called with ‘to_return = "raw_output"’.

Usage

```
from_konfound(
  x,
  dof = NULL,
  lambda = seq(0, 0.5, by = 0.01),
  treatment = NA_character_,
  index = c("IT", "RIR")
)
```

Arguments

x	A list returned by ‘konfound()’/‘pkonfound()’ with ‘to_return = "raw_output"’.
dof	Optional residual degrees of freedom (ITCV only). If supplied, the path also carries adjusted t statistics.
lambda	Numeric vector of impacts in $[0, 1)$ for ‘index = "IT"’, or of replacement proportions in $[0, 1]$ for ‘index = "RIR"’ (default ‘seq(0, 1, by = 0.001)’ when not supplied).
treatment	Optional label for the treatment.
index	“IT” (default) or “RIR”.

Details

With ‘index = "IT"’ (default), the impact threshold (ITCV) path is built from the observed and critical correlations (‘obs_r’, ‘critical_r’). With ‘index = "RIR"’, the robustness-of-inference-to-replacement path is built from ‘beta_threshold’ and ‘perc_bias_to_change’, and konfound’s ‘RIR_primary’ is carried in ‘meta\$rir’; see [rir_lm()] for the path.

Value

A ‘confoundsens’ object. For ‘index = "IT"’ it is on the correlation scale and ‘meta\$itcv’ holds the conditional ITCV (konfound’s ‘itcvGz’); for ‘index = "RIR"’ it is on the scale of the estimate and ‘meta\$perc_bias’ and ‘meta\$rir’ hold konfound’s percent bias and RIR.

See Also

[itcv_lm()], [rir_lm()]

Examples

```
k <- konfound::pkonfound(est_eff = 2, std_err = 0.4, n_obs = 100,
                          n_covariates = 3, index = "IT",
                          to_return = "raw_output")

path <- from_konfound(k)
path$meta$itcv
rir <- from_konfound(k, index = "RIR")
rir$meta$rir
```

from_sensemakr

Convert a sensemakr result to a confoundsens path

Description

Builds the partial R^2 sensitivity path from the summary statistics stored in a ‘sensemakr’ object (estimate, standard error, and residual degrees of freedom), using the same bias formulas as [sens_path_lm()]. Benchmark bounds stored in the object are attached as ‘meta\$bounds’.

Usage

```
from_sensemakr(x, lambda = seq(0, 0.5, by = 0.01), ratio = 1)
```

Arguments

x	An object of class “sensemakr” (from ‘sensemakr::sensemakr()’).
lambda	Numeric vector of confounder strengths in $[0, 1)$. Default is a grid from 0 to 0.5.
ratio	Positive scalar; ratio of the outcome-side to the treatment-side partial R^2 .

Value

A ‘confoundsens’ object.

See Also

[sens_path_lm()]

Examples

```
data("darfur", package = "sensemakr")
fit <- lm(peacefactor ~ directlyharmed + age + farmer_dar + herder_dar +
          pastvoted + hhsizes_darfur + female + village, data = darfur)
s <- sensemakr::sensemakr(fit, treatment = "directlyharmed",
                          benchmark_covariates = "female", kd = 1:3)
path <- from_sensemakr(s)
sens_report(path)
```

itcv_lm

*Impact threshold for a confounding variable from a fitted linear model***Description**

Computes Frank's (2000) impact threshold for a confounding variable (ITCV) for one coefficient of a linear model, together with the ITCV sensitivity path: the partial correlation between treatment and outcome after conditioning on a confounder whose impact $k = r_{DU}r_{YU}$ is split equally between the two correlations ($r_{DU} = r_{YU} = \sqrt{k}$).

Usage

```
itcv_lm(model, treatment, alpha = 0.05, lambda = seq(0, 0.5, by = 0.01))
```

Arguments

model	A fitted 'lm' object.
treatment	Character string naming the treatment coefficient.
alpha	Two-sided significance level used for the critical value.
lambda	Numeric vector of impacts in $[0, 1)$ at which to evaluate the path.

Details

Along this path the adjusted correlation is $(r - k)/(1 - k)$, which equals the critical correlation $r^\#$ exactly at $k = \text{ITCV} = (|r| - |r^\#|)/(1 - |r^\#|)$.

The conditional ITCV equals 'itcvGz' and the unconditional ITCV equals 'itcv' in the raw output of 'konfound::konfound()' (version 1.0).

Value

A list with elements 'r' (observed partial correlation), 'r_crit' (critical partial correlation), 'itcv' (the ITCV for a confounder's correlations *conditional on* the model covariates), 'dof', 'path' (a 'confoundsens' object on the correlation scale), 'r2xz' and 'r2yz' (the R^2 of the covariates with treatment and outcome), and 'itcv_unconditional' (the ITCV expressed in unconditional correlations, $\text{itcv} * \sqrt{(1 - r2xz) * (1 - r2yz)}$), 'benchmark_corr_product' (the impact of all covariates together, $R_{XZ}R_{YZ}$, the product of the multiple correlations), and 'itcv_ratio_to_benchmark' ($\text{itcv_unconditional} / \text{benchmark_corr_product}$). The ratio follows eq. (12) of Frank et al. (2025): values above 1 mean that an omitted variable would need a larger impact than all observed covariates together. Covariates such as pretests or fixed effects inflate the benchmark.

References

Frank, K. A. (2000). Impact of a confounding variable on a regression coefficient. *Sociological Methods & Research**, 29(2), 147–194. doi:10.1177/0049124100029002001

Frank, K. A., Maroulis, S. J., Duong, M. Q., & Kelcey, B. M. (2013). What would it take to change an inference? Using Rubin's causal model to interpret the robustness of causal inferences. *Educational Evaluation and Policy Analysis**, 35(4), 437–460. doi:10.3102/0162373713493129

Frank, K. A., Saw, G. K., Lin, Q., Xu, R., Rosenberg, J. M., Maroulis, S. J., & Staudt Willet, K. B. (2025). *A practical guide to impact threshold of a confounding variable (ITCV) and robustness of inference to replacement (RIR)* (Version 2). doi:10.31234/osf.io/pdgbz_v2

See Also

[from_konfound()], [sens_path_lm()], [rir_lm()]

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
it <- itcv_lm(fit, "am")
it$itcv
plot_robustness_curve(it$path, points = FALSE)
```

new_confoundsens	Create a confoundsens object
------------------	------------------------------

Description

Constructs a ‘confoundsens’ object — a lightweight container for storing sensitivity paths (e.g., $\theta(\lambda)$) and optional uncertainty or stratification information used by ‘confoundvis’ plotting functions.

Usage

```
new_confoundsens(
  lambda,
  theta,
  level = NULL,
  se = NULL,
  t = NULL,
  meta = list()
)
```

Arguments

lambda	Numeric vector of sensitivity strength values (e.g., ITCV lambda or delta). Should be nondecreasing; a warning is issued otherwise.
theta	Numeric vector of effect estimates along the sensitivity path. Must be the same length as ‘lambda’.
level	Optional character (or coercible) vector of subgroup (stratum) labels (e.g., “female”, “male”). Must be the same length as ‘lambda’.
se	Optional numeric vector of standard errors for ‘theta’. Must be the same length as ‘lambda’.
t	Optional numeric vector of test statistics along the path. Must be the same length as ‘lambda’.

meta Optional named list of metadata describing the path, for example ‘framework’ (“partial_r2”, “itcv”, “evaluate”, ...), ‘lambda_label’, ‘theta_label’, ‘null’ (the value of ‘theta’ that represents no effect), and ‘estimate’. Used by printing, plotting, and [sens_report()]; ignored otherwise.

Value

A ‘confoundsens’ object (a list with class “confoundsens”).

Examples

```
x <- new_confoundsens(
  lambda = seq(0, 0.2, length.out = 10),
  theta = seq(1, 0.6, length.out = 10),
  se = rep(0.1, 10)
)
x
```

plot_robustness_curve *Plot a robustness curve*

Description

Plots the sensitivity path stored in a ‘confoundsens’ object as a function of ‘lambda’. By default, plots the effect path ‘theta(lambda)’; optionally plots the test-statistic path ‘t(lambda)’. Pointwise 95 are drawn when standard errors are available.

Usage

```
plot_robustness_curve(
  x,
  what = c("theta", "t"),
  bands = TRUE,
  points = TRUE,
  facet_level = TRUE,
  reference = TRUE
)
```

Arguments

x A ‘confoundsens’ object created by [new_confoundsens()] or [as_confoundsens()].

what Character; which path to plot: “theta” (default) or “t”.

bands Logical; if ‘TRUE’ and ‘x\$se’ is present, draw 95 confidence bands (applies only when ‘what = “theta”’).

points Logical; if ‘TRUE’, overlay points on the line.

facet_level Logical; if ‘TRUE’ and ‘x\$level’ is present, facet the plot by level.

reference Logical; if 'TRUE' (default) and 'x\$meta' records a null value ('meta\$null') or a critical value ('meta\$threshold'), draw them as horizontal reference lines (dotted and dashed respectively). Objects created by [new_confoundrsens()] without 'meta' are unaffected.

Value

A [ggplot2::ggplot()] object.

Examples

```
x <- new_confoundrsens(
  lambda = seq(0, 0.2, length.out = 25),
  theta = 1 - 2 * seq(0, 0.2, length.out = 25),
  se = rep(0.05, 25),
  level = rep(c("female", "male"), length.out = 25)
)
plot_robustness_curve(x)
plot_robustness_curve(x, bands = FALSE, facet_level = FALSE)
```

plot_sensitivity_contour

Sensitivity contour plot

Description

Draws sensitivity boundaries in the plane of the two confounder correlations (r_{YU}, r_{DU}) and optionally overlays observed covariate benchmarks as labelled points.

Usage

```
plot_sensitivity_contour(
  threshold = NULL,
  grid_n = 200,
  benchmarks = NULL,
  itcv = NULL,
  limits = c(-1, 1)
)
```

Arguments

threshold Positive numeric scalar; the product threshold. The product reference satisfies $|r_{YU} \cdot r_{DU}| = \text{'threshold'}$. May be omitted when 'itcv' is supplied, in which case the conditional ITCV is used.

grid_n Integer ≥ 50 ; resolution of the curves (points per branch for the product reference; grid points per axis for the exact boundary and shading).

benchmarks	Optional data.frame with columns 'r_yu' and 'r_du' (numeric) and an optional 'label' column (character). Each row is plotted as a labelled benchmark point; labels repel one another when the ggrepel package is installed. The output of [covariate_impacts()] with 'metric = "itcv"' can be passed directly.
itcv	Optional output of [itcv_lm()] (a list with 'r' and 'r_crit'), or a list or named numeric vector with elements 'r' and 'r_crit'. When supplied, the exact boundary and the infeasible region are drawn.
limits	Numeric vector of length two; the displayed range of both axes. Narrow it (for example 'c(-0.3, 0.3)') when benchmarks lie close to the origin.

Details

Two kinds of boundary are available.

*** **Product reference**** (always drawn, dashed when an exact boundary is also drawn): the four branches of $|r_{YU}r_{DU}| = \text{'threshold'}$. With 'threshold' equal to the ITCV, this is the impact threshold of Frank (2000). It is exact for confounders whose two correlations have equal magnitude, but for unequal correlations the product alone does not determine whether significance is lost. *** **Exact boundary**** (when 'itcv' is supplied): the set of pairs at which the confounder-adjusted partial correlation

$$r_{\text{adj}} = \frac{r - r_{DU}r_{YU}}{\sqrt{(1 - r_{DU}^2)(1 - r_{YU}^2)}}$$

has magnitude equal to the critical correlation. The solid curve is the boundary in the direction of the original estimate; beyond it the estimate is no longer significant ("Not significant" shading). The dotted curve is the boundary in the reversed direction; beyond it the adjusted estimate is significant with the opposite sign. Both curves are computed in closed form. Pairs for which the correlation matrix of (D, Y, U) given the covariates would not be positive definite, $1 - r^2 - r_{DU}^2 - r_{YU}^2 + 2rr_{DU}r_{YU} \leq 0$, cannot occur and are shaded as infeasible.

Value

A [ggplot2::ggplot()] object.

References

Frank, K. A. (2000). Impact of a confounding variable on a regression coefficient. **Sociological Methods & Research**, 29(2), 147–194. doi:10.1177/0049124100029002001

Examples

```
b <- data.frame(
  r_yu = c(0.10, 0.15),
  r_du = c(0.20, 0.12),
  label = c("SES", "BMI")
)
plot_sensitivity_contour(threshold = 0.02, benchmarks = b)

# Exact boundary and infeasible region from a fitted model
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
plot_sensitivity_contour(itcv = itcv_lm(fit, "wt"))
```

plot_sensitivity_love *Sensitivity Love plot*

Description

Benchmarks a sensitivity threshold against the empirical distribution of observed covariate impacts in a "Love plot"-style display. Each covariate appears as a point on a horizontal impact axis; the sensitivity threshold is shown as a vertical reference line. Covariates to the left of the line are weaker than the threshold; those to the right pose a credible threat.

Usage

```
plot_sensitivity_love(
  df,
  threshold = attr(df, "threshold"),
  sort = TRUE,
  top = NULL
)
```

Arguments

df	A data.frame with at least two columns: * 'covariate' — covariate names (character or factor). * 'impact' — numeric impact values (e.g., ITCV product $ r_{YU} \cdot r_{DU} $, partial R^2 , or other confounding-strength metric).
threshold	Single non-missing numeric value. Defaults to the "threshold" attribute of 'df', which [covariate_impacts()] sets. Drawn as a vertical reference line (the sensitivity threshold). Rows with missing 'impact' are dropped.
sort	Logical; if 'TRUE' (default), sort covariates by 'impact' on the y-axis (ascending).
top	Optional positive integer. If supplied, only the 'top' covariates with the largest absolute impact are displayed.

Value

A [ggplot2::ggplot()] object.

Examples

```
df <- data.frame(
  covariate = c("SES", "BMI", "Gender", "Race", "Age"),
  impact    = c(0.12, 0.05, 0.02, 0.08, 0.03)
)
plot_sensitivity_love(df, threshold = 0.10)
plot_sensitivity_love(df, threshold = 0.10, top = 3)

# From a fitted model: threshold is taken from covariate_impacts()
fit <- lm(mpg ~ am + wt + hp + qsec, data = mtcars)
plot_sensitivity_love(covariate_impacts(fit, "am"))
```

plot_sensitivity_surface

Plot a two-parameter sensitivity surface

Description

Draws a `[sens_surface()]` object: shaded zones where the conclusion changes, the boundaries (solid for loss of significance, dotted for significance in the reversed direction, dashed for the null), and optional benchmark points. Unshaded cells are those where the original conclusion holds.

Usage

```
plot_sensitivity_surface(x, benchmarks = NULL, bounds = TRUE)
```

Arguments

x	A 'confoundsurf' object.
benchmarks	Optional data frame of reference points with columns 'a' and 'b' (and optionally 'label') on the axes of the surface. For a partial- R^2 surface, the output of 'covariate_impacts(..., metric = "partial_r2")' is accepted (columns 'r2dz.x' and 'r2yz.dx'); for an ITCV surface, the output of 'covariate_impacts(..., metric = "itcv")' (columns 'r_du' and 'r_yu'). For a surface built from a 'sensemakr' path, its formal bounds are added automatically unless 'bounds = FALSE'.
bounds	Logical; draw 'sensemakr' formal bounds when present.

Value

A `[ggplot2::ggplot()]` object.

See Also

[`sens_surface()`]

Examples

[illegible]

<code>print.confoundsens</code>	<i>Print method for confoundsens objects</i>
---------------------------------	--

Description

Prints a concise summary of the key fields in a ‘confoundsens’ object.

Usage

```
## S3 method for class 'confoundsens'
print(x, ...)
```

Arguments

<code>x</code>	A ‘confoundsens’ object.
<code>...</code>	Unused; included for S3 method consistency.

Value

‘x’, invisibly.

Examples

```
x <- new_confoundsens(
  lambda = seq(0, 0.2, length.out = 5),
  theta = seq(1, 0.8, length.out = 5)
)
print(x)
```

<code>rir_lm</code>	<i>Robustness of inference to replacement (RIR) from a linear model</i>
---------------------	---

Description

Computes the robustness of inference to replacement of Frank et al. (2013) for a coefficient in a fitted linear model, and the corresponding path. Suppose a proportion λ of the cases were replaced by cases in which the treatment has no effect. The estimate would then be $(1 - \lambda)\hat{\beta}$. The inference is nullified when this reaches the threshold for statistical significance $\beta^\# = \text{sign}(\hat{\beta}) t_{\text{crit}} SE$, with the standard error held fixed. The crossing $1 - \beta^\# / \hat{\beta}$ is the proportion of the estimate that would have to be due to bias, and RIR is the number of cases this represents. The calculation follows ‘konfound::konfound()’ with ‘index = “RIR”’, using the residual degrees of freedom of the model.

Usage

```
rir_lm(
  model,
  treatment,
  alpha = 0.05,
  lambda = seq(0, 1, by = 0.001),
  threshold = NULL
)
```

Arguments

model	A fitted 'lm' object.
treatment	Character string naming the treatment coefficient (a column of the model matrix).
alpha	Two-sided significance level.
lambda	Numeric vector of replacement proportions in $\backslash[0, 1\backslash]$.
threshold	Optional effect threshold on the scale of the estimate (for example, the smallest effect that would justify a policy). When supplied, it replaces the significance threshold, as with 'eff_thr' in konfound; its sign is taken from the estimate.

Value

A list with 'estimate', 'beta_threshold', 'perc_bias' (percent of the estimate that would have to be due to bias), 'rir' (number of cases), 'n_obs', and 'path', a 'confoundsens' object whose 'lambda_sig' in `[robustness_points()]` equals 'perc_bias / 100'. For an estimate that is not significant, 'perc_bias' and 'rir' are 'NA'; 'konfound' reports the corresponding replacement needed to sustain an inference.

References

Frank, K. A., Maroulis, S. J., Duong, M. Q., & Kelcey, B. M. (2013). What would it take to change an inference? Using Rubin's causal model to interpret the robustness of causal inferences. **Educational Evaluation and Policy Analysis**, 35(4), 437–460. doi:[10.3102/0162373713493129](https://doi.org/10.3102/0162373713493129)

Frank, K. A., Saw, G. K., Lin, Q., Xu, R., Rosenberg, J. M., Maroulis, S. J., & Staudt Willet, K. B. (2025). **A practical guide to impact threshold of a confounding variable (ITCV) and robustness of inference to replacement (RIR)** (Version 2). doi:[10.31234/osf.io/pdgbz_v2](https://doi.org/10.31234/osf.io/pdgbz_v2)

See Also

`[itcv_lm()]`, `[from_konfound()]`

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
rr <- rir_lm(fit, "wt")
rr[c("beta_threshold", "perc_bias", "rir")]
# a substantive threshold instead of statistical significance
rir_lm(fit, "wt", threshold = 2)$rir
sens_report(rr$path)
```

robustness_points	<i>Locate robustness thresholds along a sensitivity path</i>
-------------------	--

Description

Finds, for each level of a ‘confoundsens’ object, the confounder strength λ at which (i) the point estimate reaches the null value and (ii) statistical significance is lost. Crossings are located by linear interpolation between grid points, so their precision depends on the spacing of ‘lambda’.

Usage

```
robustness_points(x, alpha = 0.05)
```

Arguments

x	A ‘confoundsens’ object.
alpha	Two-sided significance level.

Details

The significance criterion is chosen from what the object carries, in this order: a critical value on the ‘theta’ scale in ‘meta\$threshold’ (ITCV paths); adjusted t statistics with residual degrees of freedom in ‘meta\$dof’ (partial R^2 paths; critical value from a t distribution with ‘dof - 1’ degrees of freedom, as in Cinelli and Hazlett, 2020); standard errors (normal critical value); or t statistics without degrees of freedom (normal critical value).

Value

A data frame with columns ‘level’, ‘theta_start’, ‘lambda_null’, ‘lambda_sig’, and ‘sig_rule’. ‘NA’ means the crossing is not reached within the supplied ‘lambda’ range.

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
robustness_points(sens_path_lm(fit, "am", lambda = seq(0, 0.9, by = 0.001)))
```

sens_path_lm	<i>Sensitivity path from a fitted linear model (partial R-squared framework)</i>
--------------	--

Description

Computes the bias-adjusted treatment coefficient as a function of the strength of a hypothetical omitted confounder, using the omitted-variable bias formulas of Cinelli and Hazlett (2020). Confounder strength is indexed by λ , the partial R^2 of the confounder with the treatment ($R^2_{D \sim Z|X}$); the partial R^2 with the outcome is $R^2_{Y \sim Z|D,X} = \min(\text{ratio} \times \lambda, 1)$. The default ‘ratio = 1’ gives the equal-strength path along which the robustness value is defined.

Usage

```
sens_path_lm(model, treatment, lambda = seq(0, 0.5, by = 0.01), ratio = 1)
```

Arguments

model	A fitted ‘lm’ object.
treatment	Character string naming the treatment coefficient (a column of the model matrix).
lambda	Numeric vector of confounder strengths in $[0, 1]$. Default is a grid from 0 to 0.5.
ratio	Positive scalar; ratio of the outcome-side to the treatment-side partial R^2 .

Details

The confounder is assumed to act in the direction that shrinks the estimate toward zero (the conventional worst case for a reported effect).

Value

A ‘confoundsens’ object with ‘theta’ (adjusted estimate), ‘se’ (adjusted standard error), and ‘t’ (adjusted t statistic), plus ‘meta’ recording the original estimate, degrees of freedom, and robustness value.

References

Cinelli, C., & Hazlett, C. (2020). Making sense of sensitivity: Extending omitted variable bias. *Journal of the Royal Statistical Society: Series B**, 82(1), 39–67. doi:10.1111/rssb.12348

See Also

```
[from_sensemkr()], [itcv_lm()], [covariate_impacts()]
```

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
path <- sens_path_lm(fit, treatment = "am")
path
plot_robustness_curve(path, points = FALSE)
```

sens_path_pairs	<i>Rosenbaum sensitivity path for matched pairs</i>
-----------------	---

Description

Computes a sensitivity path for a matched-pair observational study under the sensitivity model of Rosenbaum (2002): within a pair, the odds of treatment for the two units may differ by at most a factor $\Gamma \geq 1$. For each value of Γ , the function computes the sharp upper bound on the one-sided P-value of a randomization test of no effect and stores it as an equivalent standard normal deviate, so that the path can be drawn, located, tabulated, and reported with the same functions as the other frameworks.

Usage

```
sens_path_pairs(
  d,
  gamma = seq(1, 3, by = 0.01),
  method = c("wilcoxon", "binary"),
  alpha = 0.05
)
```

Arguments

d	Numeric vector of treated-minus-control differences, one per matched pair. For ‘method = "binary"’, values must be in {-1, 0, 1}.
gamma	Numeric vector of sensitivity parameters, all ‘>= 1’.
method	“wilcoxon” (default) or “binary”.
alpha	One-sided significance level used for the stored threshold and the sensitivity value.

Details

Two statistics are available. ‘method = "wilcoxon"’ uses Wilcoxon’s signed rank statistic with the large-sample approximation of Rosenbaum (2002, Sec. 4.3.3), computed as in ‘DOS2::senWilcox()’: all absolute differences are ranked (ties receive average ranks) and zero differences then receive rank zero. When some differences are zero, the statistic and P-values therefore differ from those of ‘wilcox.test()’ and ‘rbounds::psens()’, which drop zeros before ranking. ‘method = "binary"’ is for a binary outcome (differences in {-1, 0, 1}) and uses the exact binomial bound for McNemar’s statistic (Rosenbaum 2002, Sec. 4.3.2), which agrees with ‘sensitivity2x2xk::mh()’ applied to the pairs as strata.

The test is one-sided in the direction of ‘d > 0’ (treated minus control). Supply ‘-d’ to test the opposite direction.

Value

A ‘confoundsens’ object with ‘lambda’ = Γ and ‘theta’ = the standard normal deviate equivalent to the upper-bound P-value. ‘meta\$threshold’ is ‘qnorm(1 - alpha)’, so [robustness_points()] reports as ‘lambda_sig’ the value of Γ at which the upper bound reaches ‘alpha’, and as ‘lambda_null’ the value at which it reaches 0.5. ‘meta\$sens_value’ holds the sensitivity value computed by root finding rather than on the grid, and ‘meta\$pvalue’ the upper-bound P-values along the grid.

References

Rosenbaum, P. R. (2002). **Observational Studies** (2nd ed.). Springer. doi:10.1007/97814757-36922

See Also

[robustness_points()], [sens_table()]

Examples

```
set.seed(1)
d <- rnorm(60, mean = 0.5)
p <- sens_path_pairs(d, gamma = seq(1, 4, by = 0.01))
robustness_points(p)
sens_report(p)

# Binary outcome: 30 discordant pairs, 22 with the event in the treated unit
db <- c(rep(1, 22), rep(-1, 8), rep(0, 50))
robustness_points(sens_path_pairs(db, seq(1, 3, by = 0.01), method = "binary"))
```

sens_report	<i>Plain-language sensitivity report</i>
-------------	--

Description

Summarises a ‘confoundsens’ path in a few sentences: the starting estimate, the framework-specific summary (robustness value, ITCV, or E-value) when available, and the confounder strengths at which the point estimate reaches the null and significance is lost. The report closes with a statement of what the analysis cannot establish.

Usage

```
sens_report(x, alpha = 0.05, digits = 3)
```

Arguments

x	A ‘confoundsens’ object.
alpha	Two-sided significance level.
digits	Number of significant digits.

Value

An object of class ‘confoundvis_report’: a list with ‘text’ (a character vector) and ‘points’ (the output of [robustness_points()]). It prints as text.

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
sens_report(sens_path_lm(fit, "am", lambda = seq(0, 0.9, by = 0.001)))
```

sens_surface	<i>Two-parameter sensitivity surface</i>
--------------	--

Description

Returns the two-parameter sensitivity surface of which a ‘confoundsens’ path is one slice. The horizontal axis is always the confounder’s association with treatment and the vertical axis its association with the outcome, each in the units of the framework:

Usage

```
sens_surface(x, a = NULL, b = NULL, n = 201, alpha = 0.05)
```

Arguments

x	A ‘confoundsens’ object produced by [sens_path_lm()], [from_sensemkr()], [itcv_lm()] (its ‘\$path’), [from_konfound()] with ‘index = "IT"', [from_evalue()], or [sens_path_pairs()].
a, b	Optional numeric grids for the two axes. Defaults depend on the framework and extend beyond the relevant boundary.
n	Number of grid points per axis when ‘a’ or ‘b’ is not supplied.
alpha	Significance level for the partial- R^2 boundary. ITCV and Rosenbaum paths use the level stored in the path (a warning is given if ‘alpha’ is supplied); for E-values the boundary is defined by the stored confidence limit.

Details

| Framework | ‘a’ (treatment side) | ‘b’ (outcome side) | Value | |—|—|—|—| | ‘partial_r2’ | $R^2_{D \sim U|X}$
| $R^2_{Y \sim U|D,X}$ | adjusted estimate | | ‘itcv’ | $r_{DU|X}$ | $r_{YU|X}$ | adjusted partial correlation | | ‘evalue’ |
 RR_{UD} | RR_{UY} | bound on the risk ratio | | ‘rosenbaum’ | Λ | Δ | implied Γ |

Each surface carries boundaries computed from the published formula of the framework, in closed form where one exists and otherwise by root finding (the partial- R^2 significance boundaries, and the Rosenbaum Γ at which the upper-bound P-value is 0.5): the **“null boundary”**, where the point estimate (or, for Rosenbaum, the upper-bound P-value of 0.5) is reached, and the **“significance boundary”**, where the conclusion at level ‘alpha’ is lost. For the partial- R^2 framework, the bias and adjusted standard error of Cinelli and Hazlett (2020) are used, with $d - 1$ degrees of freedom for the significance boundary. For the ITCV, the boundaries are those of [plot_sensitivity_contour()].

For E-values, the joint bounding factor $B = RR_{UD}RR_{UY}/(RR_{UD} + RR_{UY} - 1)$ of Ding and VanderWeele (2016) is used, so the null boundary passes through the point (E-value, E-value). For Rosenbaum's model, $\Gamma = (\Lambda\Delta + 1)/(\Lambda + \Delta)$ (Rosenbaum and Silber, 2009), so the significance boundary is the set of (Λ, Δ) pairs that amplify the sensitivity value.

Each surface is the two-parameter display that the source framework already uses: the partial- R^2 surface is the plane of 'sensemakr::ovb_contour_plot()', the E-value surface is the curve of equivalent confounders shown by 'EValue::bias_plot()', and the Rosenbaum surface gives the pairs returned by 'sensitivymv::amplify()'. The ITCV surface plots the adjusted partial correlation of Frank (2000) over both correlations. The surface only evaluates these published formulas. It reports no area or share of the plane: the size of a shaded zone depends on the chosen axis ranges and has no inferential meaning.

Value

An object of class 'confoundsurf': a list with 'grid' (a data frame with columns 'a', 'b', 'value', and 'zone'), 'boundary' (a data frame with columns 'a', 'b', 'kind', and 'group'), and 'meta' (framework, axis labels, and the quantities used). Plot it with [plot_sensitivity_surface()].

References

- Cinelli, C., & Hazlett, C. (2020). Making sense of sensitivity: Extending omitted variable bias. **Journal of the Royal Statistical Society: Series B**, 82(1), 39–67. doi:10.1111/rssb.12348
- Ding, P., & VanderWeele, T. J. (2016). Sensitivity analysis without assumptions. **Epidemiology**, 27(3), 368–377. doi:10.1097/EDE.0000000000000457
- Frank, K. A. (2000). Impact of a confounding variable on a regression coefficient. **Sociological Methods & Research**, 29(2), 147–194. doi:10.1177/0049124100029002001
- Rosenbaum, P. R., & Silber, J. H. (2009). Amplification of sensitivity analysis in matched observational studies. **Journal of the American Statistical Association**, 104(488), 1398–1405. doi:10.1198/jasa.2009.tm08470

See Also

[plot_sensitivity_surface()]

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
s <- sens_surface(sens_path_lm(fit, "wt"))
s
plot_sensitivity_surface(s)

# E-value: every pair of risk ratios that explains away the estimate
if (requireNamespace("EValue", quietly = TRUE)) {
  e <- EValue::evaluates.RR(1.8, lo = 1.3, hi = 2.5)
  plot_sensitivity_surface(sens_surface(from_evalue(e)))
}
```

sens_table	<i>Summarize several sensitivity paths in one table</i>
------------	---

Description

Collects the decision information of several ‘confoundsens’ objects into one data frame: for each path (and each level within a path), the framework, the meaning of its sensitivity parameter, the framework’s own summary statistic, and the confounder strengths at which the null and the significance boundary are reached, together with the rule used to locate the latter. The table is intended for reporting several analyses of the same study side by side. It does not convert the sensitivity parameters to a common scale: values in the ‘lambda_null’ and ‘lambda_sig’ columns are comparable only within a row.

Usage

```
sens_table(..., alpha = 0.05)
```

Arguments

...	‘confoundsens’ objects, or a single list of them. Names (from ‘name = object’ arguments or list names) are used as row labels.
alpha	Two-sided significance level passed to [robustness_points()] for paths without a stored threshold. Paths with a stored threshold (ITCV, Rosenbaum) use the level they were built with.

Value

A data frame of class ‘confoundvis_table’ with columns ‘path’, ‘level’, ‘framework’, ‘source’, ‘parameter’ (meaning of lambda), ‘summary_name’, ‘summary_value’, ‘theta_start’, ‘lambda_null’, ‘lambda_sig’, and ‘sig_rule’. It prints with a reminder that rows use different scales.

See Also

[robustness_points()], [sens_report()]

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
g <- seq(0, 0.9, by = 0.001)
sens_table(partial_r2 = sens_path_lm(fit, "wt", lambda = g),
           itcv       = itcv_lm(fit, "wt", lambda = g)$path)
```

summary.confoundsens *Summary method for confoundsens objects*

Description

Produces a concise numerical summary of the sensitivity path, optionally broken down by level.

Usage

```
## S3 method for class 'confoundsens'  
summary(object, ...)
```

Arguments

object	A 'confoundsens' object.
...	Unused; included for S3 method consistency.

Value

An object of class 'summary.confoundsens' containing a 'table' data.frame with per-level summary statistics.

Examples

```
x <- new_confoundsens(  
  lambda = seq(0, 0.2, length.out = 10),  
  theta = seq(1, 0.6, length.out = 10),  
  se = rep(0.08, 10),  
  level = rep(c("female", "male"), length.out = 10)  
)  
summary(x)
```

Index

`as.data.frame.confoundsens`, [2](#)
`as_confoundsens`, [3](#)

`covariate_impacts`, [4](#)

`from_evalue`, [6](#)
`from_konfound`, [7](#)
`from_sensemakr`, [8](#)

`itcv_lm`, [9](#)

`new_confoundsens`, [10](#)

`plot_robustness_curve`, [11](#)
`plot_sensitivity_contour`, [12](#)
`plot_sensitivity_love`, [14](#)
`plot_sensitivity_surface`, [15](#)
`print.confoundsens`, [16](#)

`rir_lm`, [16](#)
`robustness_points`, [18](#)

`sens_path_lm`, [18](#)
`sens_path_pairs`, [20](#)
`sens_report`, [21](#)
`sens_surface`, [22](#)
`sens_table`, [24](#)
`summary.confoundsens`, [25](#)