

Package ‘iSTATS’

October 10, 2026

Type Package

Title A Graphical Interface to Perform STOCsY Analyses on NMR Data

Version 1.8

Date 2026-10-09

Description Launches a 'shiny' based application for Nuclear Magnetic Resonance (NMR) data importation and Statistical Total Correlation Spectroscopy (STOCsY) analyses in a full interactive approach. The theoretical background and applications of the STOCsY method are described by Cloarec, O., Dumas, M. E., Craig, A., Barton, R. H., Trygg, J., Hudson, J., Blancher, C., Gauguier, D., Lindon, J. C., Holmes, E. & Nicholson, J. (2005) <doi:10.1021/ac048630x>. Spectral alignment follows the interval correlation optimized shifting method of Savorani, F., Tomasi, G. & Engelsen, S. B. (2010) <doi:10.1016/j.jmr.2009.11.012>.

Depends R(>= 3.6), shinyBS(>= 0.61), shinyWidgets(>= 0.4.3)

Imports data.table, ggplot2(>= 3.0.0), gtools(>= 3.8.1), shiny(>= 1.6.0), stats, utils

BugReports <https://github.com/vitor-mendes-iq/iSTATS/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

NeedsCompilation no

License GPL (>= 3)

Author Luiz Henrique Keng Queiroz Junior [aut, cre],
Vitor Mendes de Oliveira [aut],
Renan Ziemann Wilhelms [aut]

Maintainer Luiz Henrique Keng Queiroz Junior <keng@ufg.br>

Repository CRAN

Date/Publication 2026-10-10 15:00:09 UTC

Contents

CS_values_real	2
file_names	2
icoshift	3
iSTATS	4
NMRData	5

Index	6
-------	---

CS_values_real	Matrix of NMR chemical shifts
----------------	-------------------------------

Description

A matrix containing all chemical shifts of NMR data milk samples

Usage

CS_values_real

Format

A matrix with 11 rows and 32778 variables:

file_names	A list of sample names
------------	------------------------

Description

A list of sample names

Usage

file_names

Format

A list of string with sample names

icoshift

*Align Spectra with Interval Correlation Optimized Shifting***Description**

Splits spectra into intervals and rigidly shifts each interval to maximize its cross-correlation with a target. Samples must be rows and spectral points must be columns.

Usage

```
icoshift(xT, xP, inter = "whole", n = NULL, options = NULL, Scal = NULL)
```

Arguments

xT	A numeric target with one value per column of xP, or one of "average", "average2", "median", or "max". "average2" uses a fixed multiplier of 3.
xP	Numeric matrix with samples in rows and spectral points in columns.
inter	"whole"; an integer number of intervals; a character interval length or range; or a numeric vector of start/end pairs. Numeric values refer to points unless options[5] is 1.
n	Positive maximum shift, "f" for fast automatic search, or "b" for the more exhaustive search. Numeric values use points or scale units according to options[5].
options	Numeric vector or named list with show, fill, preCOSHift, maxPreCOSHift, useScal, and alignPreprocessed. Defaults are c(1, 1, 0, 0, 0, 0). Preprocessing values are 0 (raw), 1 (SNV), 3 (the original msc(0, A) behavior), -1, or -2 (derivatives).
Scal	Optional strictly monotonic axis with one value per column. Used for conversion when options[5] is 1; it is not modified.

Details

This implementation covers one-dimensional spectra, not MATLAB `icoshiftMC`. `show=2` does not create the MATLAB diagnostic plot. The "b" search may be slow, overlapping intervals are not reconciled, and repeated boundary filling can create edge artifacts. Character ranges use - as separator and cannot express negative endpoints; use numeric pairs. See `system.file("ICOSHIFT.md", package = "iSTATS")` for the app workflow.

Value

A list containing aligned matrix `xCS`, interval table `ints`, shift indices `ind` (positive is left, negative is right), and actual target.

References

Savorani F, Tomasi G, Engelsen SB (2010). "icoshift: A versatile tool for the rapid alignment of 1D NMR spectra." *Journal of Magnetic Resonance*, 202(2), 190-202. doi:10.1016/j.jmr.2009.11.012.

Examples

```
axis <- seq(1, -1, length.out = 64)
target <- dnorm(seq(-3, 3, length.out = 64))
spectra <- rbind(target, c(target[-1], 0), c(0, target[-64]))

fit <- icoshift("average", spectra, c(1, 64), n = 3,
               options = c(0, 1, 0, 0, 0, 0))
dim(fit$xCS)
fit$ind

fit_ppm <- icoshift("average", spectra, c(-0.5, 0.5), n = "f",
                   options = c(0, 1, 0, 0, 1, 1), Scal = axis)
```

iSTATS

A Graphical Interface to Perform STOCSY analyses on NMR Data

Description

Statistical T_{OTAL} Correlation Spectroscop_Y (STOCSY) is a method developed to analyze 1D Nuclear Magnetic Resonance (NMR) data, with many applications in metabolomic science, as to help the identification of molecules in complex mixture. Although STOCSY is promising method, its use requires some programming language skills. To overcome this challenge we developed the interactive STATistical Spectroscopy (iSTATS) package, based on 'shiny', in which it is possible to perform STOCSY analyses in a full interactive way, from 1D NMR matrix construction to select specific regions to apply STOCSY methods more accurately.

Usage

```
iSTATS()
```

Value

No return value. The function is called for its side effect of launching the 'shiny' application, and returns invisibly when the application is closed.

Examples

```
if(interactive()){iSTATS::iSTATS()}
```

NMRData

*Matrix of NMR intensities***Description**

A matrix containing the intensities of NMR data milk samples

Usage

NMRData

Format

A matrix with 11 rows and 32778 variables:

Index

* **datasets**

CS_values_real, [2](#)

file_names, [2](#)

NMRData, [5](#)

CS_values_real, [2](#)

file_names, [2](#)

icoshift, [3](#)

iSTATS, [4](#)

NMRData, [5](#)