

Package ‘missingHE’

October 13, 2026

Type Package

Title Missing Cost Effectiveness Models

Version 1.6.2

Description Performs Bayesian cost-effectiveness analysis with missing outcome data. Three classes of models can be fitted under a variety of missing data assumptions: selection models, pattern mixture models and hurdle models. The package allows to assess model convergence and summarise the statistical and economic results using different types of measures and graphs. The methods implemented are described in Mason (2018) <[doi:10.1002/hec.3793](https://doi.org/10.1002/hec.3793)>, Molenberghs (2000) <[doi:10.1007/978-1-4419-0300-6_18](https://doi.org/10.1007/978-1-4419-0300-6_18)> and Gabrio (2019) <[doi:10.1002/sim.8045](https://doi.org/10.1002/sim.8045)>.

Depends R (>= 4.1.0)

Suggests knitr, rmarkdown, bookdown, devtools

VignetteBuilder knitr

URL <https://github.com/AnGabrio/missingHE>

License GPL-2

Encoding UTF-8

BugReports <https://github.com/AnGabrio/missingHE/issues/>

LazyData true

Imports ggpubr, ggmcmc, ggthemes, BCEA, ggplot2, bayesplot, methods, R2jags, loo, coda, mcmc

Config/roxygen2/version 8.1.0

Maintainer Andrea Gabrio <a.gabrio@maastrichtuniversity.nl>

Repository CRAN

NeedsCompilation no

Author Andrea Gabrio [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0002-7650-4534>>)

Date/Publication 2026-10-13 16:10:02 UTC

Contents

coef.missingHE	2
diagnostic	3
hurdle	6
lmdm	11
MenSS	16
pattern	18
PBS	23
pic	25
plot.missingHE	27
postsum	29
ppc	29
print.missingHE	31
selection	32
summary.missingHE	37
Index	39

coef.missingHE	<i>Extract regression coefficient estimates from objects in the class missingHE</i>
----------------	---

Description

Produces a table printout with summary statistics for the regression coefficients of the health economic evaluation probabilistic model run using the function [selection](#), [pattern](#), [hurdle](#) or [lmdm](#).

Usage

```
## S3 method for class 'missingHE'
coef(object, prob = c(0.025, 0.975), random = FALSE, digits = 3, ...)
```

Arguments

object	A missingHE object containing the results of the Bayesian modelling and the economic evaluation
prob	A numeric vector of probabilities within the range (0,1), representing the upper and lower CI sample quantiles to be calculated and returned for the estimates.
random	Logical. If random is TRUE, the estimates of the random effects parameters are printed, when available.
digits	Integer indicating the number of decimal places to be used for rounding (default = 3).
...	Additional arguments affecting the summary produced.

Value

Prints a table with some summary statistics, including posterior mean, standard deviation and lower and upper quantiles based on the values specified in `prob`, for the posterior distributions of the regression coefficients of the effects and costs models run using the function `selection`, `pattern`, `hurdle` or `lmdm`.

Author(s)

Andrea Gabrio

See Also

[selection](#) [pattern](#) [hurdle](#) [lmdm](#) [diagnostic](#) [plot.missingHE](#)

Examples

```
# For examples see the function \code{\link{selection}}, \code{\link{pattern}},
# \code{\link{hurdle}} or \code{\link{lmdm}}
#
#
```

diagnostic

Diagnostic checks for assessing MCMC convergence of Bayesian models fitted in JAGS using the function [selection](#), [pattern](#), [hurdle](#) or [lmdm](#).

Description

The focus is restricted to full Bayesian models in cost-effectiveness analyses based on the function [selection](#), [pattern](#), [hurdle](#) and [lmdm](#), with convergence of the MCMC chains that is assessed through graphical checks of the posterior distribution of the parameters of interest. Examples are density plots, trace plots, autocorrelation plots, etc. Other types of posterior checks are related to some summary MCMC statistics that are able to detect possible issues in the convergence of the algorithm, such as the potential scale reduction factor or the effective sample size. Different types of diagnostic tools and statistics are used to assess model convergence using functions contained in the package **ggmcmc**. Graphics and plots are managed using functions contained in the package **ggplot2** and **ggthemes**.

Usage

```
diagnostic(x, type = "denplot", param = "all", theme = NULL, ...)
```

Arguments

x	An object of class "missingHE" containing the posterior results of a full Bayesian model implemented using the function selection , pattern , hurdle or lmdm .
type	Type of diagnostic check to be plotted for the model parameter selected. Available choices include: 'histogram' for histogram plots, 'denplot' for density plots, 'traceplot' for trace plots, 'acf' for autocorrelation plots, 'running' for running mean plots, 'compare' for comparing the distribution of the whole chain with only its last part, 'cross' for cross correlation plots, 'Rhat' for the potential scale reduction factor, 'geweke' for the geweke diagnostic, 'pairs' for posterior correlation among the parameters, 'caterpillar' for caterpillar plots.
param	Name of the family of parameters to process, as given by a regular expression. For example the mean parameters for the effect and cost variables can be specified using 'mu.e' and 'mu.c', respectively. Different types of models may have different parameters depending on the assumed distributions and missing data assumptions. To see a complete list of all possible parameters by types of models assumed see details.
theme	Type of ggplot theme among some pre-defined themes, mostly taken from the package ggthemes . For a full list of available themes see details.
...	Additional parameters that can be provided to manage the graphical output of diagnostic.

Details

Depending on the types of plots specified in the argument `type`, the output of `diagnostic` can produce different combinations of MCMC visual posterior checks for the family of parameters indicated in the argument `param`. For a full list of the available plots see the description of the argument `type` or see the corresponding plots in the package **ggmcmc**.

The parameters that can be assessed through `diagnostic` are only those included in the object `x` (see Arguments). Specific character names must be specified in the argument `param` according to the specific model implemented. The available names and the parameters associated with them are:

- "mu.e" the mean of the effects across treatment arms.
- "mu.c" the mean of the costs across treatment arms.
- "sd.e" the standard deviation of the effects.
- "sd.c" the standard deviation of the costs.
- "alpha" the regression coefficients for the effects.
- "beta" the regression coefficients for the costs.
- "beta.f" the regression coefficients for the costs related to the effects predictor.
- "alpha.time" the autoregressive coefficients for the effects (only with the function `lmdm`).
- "beta.time" the autoregressive coefficients for the costs (only with the function `lmdm`).
- "random.alpha" the regression random effects coefficients for the effects.
- "random.beta" the regression random effects coefficients for the costs.
- "random.alpha.time" the autoregressive random effects coefficients for the effects (only with the function `lmdm`).

- "random.beta.time" the autoregressive random effects coefficients for the costs (only with the function `lmdm`).
- "p.e" the probability of missingness or structural values for the effects (only with the function `selection`, `hurdle` or `lmdm`).
- "p.c" the probability of missingness or structural values for the costs (only with the function `selection`, `hurdle` or `lmdm`).
- "gamma.e" the regression coefficients of missingness or structural values for the effects (only with the function `selection`, `hurdle`).
- "gamma.c" the regression coefficient of missingness or structural values for the costs (only with the function `selection`, `hurdle`).
- "random.gamma.e" the random effects regression coefficients of missingness or structural values for the effects (only with the function `selection`, `hurdle` or `lmdm`).
- "random.gamma.c" the random effects regression coefficients of missingness or structural values for the costs (only with the function `selection`, `hurdle` or `lmdm`).
- "pattern" the probabilities of the missingness patterns (only with the function `pattern`).
- "delta.e" the mmar parameter for the effects (only with the function `selection`, `pattern` or `lmdm`).
- "delta.c" the mmar parameters for the costs (only with the function `selection`, `pattern` or `lmdm`).
- "random.delta.e" the random effects mmar parameters for the effects (only with the function `selection` or `lmdm`).
- "random.delta.c" the random effects mmar parameters for the costs (only with the function `selection` or `lmdm`).
- "all" all available parameters stored in `x`.

When the object `x` is created using the function `pattern`, pattern-specific standard deviation ("sd.e", "sd.c") and regression coefficient parameters ("alpha", "beta") for both outcomes can be visualised. The parameters associated with a missingness mechanism can be accessed only when `x` is created using the function `selection`, `pattern` or `lmdm`, while the parameters associated with the model for the structural values mechanism can be accessed only when `x` is created using the function `hurdle`.

The argument `theme` allows to customise the graphical output of the plots generated by `diagnostic` and allows to choose among a set of possible pre-defined themes taken from the package **ggtheme**. For a complete list of the available character names for each theme, see **ggthemes**.

Value

A **ggplot** object containing the plots specified in the argument `type`

Author(s)

Andrea Gabrio

References

- Gelman, A. Carlin, JB., Stern, HS. Rubin, DB.(2003). *Bayesian Data Analysis, 2nd edition*, CRC Press.
- Brooks, S. Gelman, A. Jones, JL. Meng, XL. (2011). *Handbook of Markov Chain Monte Carlo*, CRC/Chapman and Hall.

See Also

[ggs selection pattern hurdle lmdm](#).

Examples

```
# For examples see the function \code{\link{selection}}, \code{\link{pattern}},
# \code{\link{hurdle}} or \code{\link{lmdm}}
#
#
```

hurdle	<i>Full Bayesian Models to handle missingness in Economic Evaluations (Hurdle Models)</i>
--------	---

Description

Full Bayesian cost-effectiveness models to handle missing data in the outcomes using Hurdle models under a variety of alternative parametric distributions for the effect and cost variables. Alternative assumptions about the mechanisms of the structural values are implemented using a hurdle approach. The analysis is performed using the BUGS language, which is implemented in the software JAGS using the function [jags](#). The output is stored in an object of class 'missingHE'.

Usage

```
hurdle(
  data,
  model.eff,
  model.cost,
  model.se = se ~ 1,
  model.sc = sc ~ 1,
  se = 1,
  sc = 0,
  dist_e,
  dist_c,
  type,
  prob = c(0.025, 0.975),
  n.chains = 2,
  n.iter = 10000,
  n.burnin = floor(n.iter/2),
  inits = NULL,
```

```

n.thin = 1,
save_model = FALSE,
prior = "default",
center = FALSE,
...
)

```

Arguments

<code>data</code>	A data frame in which to find the variables supplied in <code>model.eff</code> , <code>model.cost</code> (model formulas for effects and costs) and <code>model.se</code> , <code>model.sc</code> (model formulas for the structural effect and cost models). Among these, effectiveness, cost and treatment indicator (only two arms) variables must always be provided and named 'e', 'c' and 'trt', respectively.
<code>model.eff</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic effectiveness outcome ('e') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.cost</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic cost outcome ('c') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. A joint bivariate distribution for effects and costs can be specified by including 'e' on the right-hand side of the formula for the costs model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.se</code>	A formula expression in conventional R linear modelling syntax. The response must be indicated with the term 'se'(structural effects). Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "probability" parameter for the structural effects through a logistic-linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.sc</code>	A formula expression in conventional R linear modelling syntax. The response must be indicated with the term 'sc'(structural costs). Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "probability" parameter for the structural costs through a logistic-linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>se</code>	Structural value to be found in the effect variables defined in <code>data</code> . If set to NULL, no structural value is chosen and a standard model for the effects is run.

<code>sc</code>	Structural value to be found in the cost variables defined in data. If set to NULL, no structural value is chosen and a standard model for the costs is run.
<code>dist_e</code>	Distribution assumed for the effects. Current available choices are: Normal ('norm'), Beta ('beta'), Gamma ('gamma'), Exponential ('exp'), Weibull ('weib'), Logistic ('logis'), Poisson ('pois'), Negative Binomial ('negbin') or Bernoulli ('bern').
<code>dist_c</code>	Distribution assumed for the costs. Current available choices are: Normal ('norm'), Gamma ('gamma') or LogNormal ('lnorm').
<code>type</code>	Type of structural value mechanism assumed. Choices are Structural Completely At Random (SCAR), and Structural At Random (SAR).
<code>prob</code>	A numeric vector of probabilities within the range (0, 1), representing the upper and lower CI sample quantiles to be calculated and returned for the imputed values.
<code>n.chains</code>	Number of chains.
<code>n.iter</code>	Number of iterations.
<code>n.burnin</code>	Number of warmup iterations.
<code>inits</code>	A list with elements equal to the number of chains selected; each element of the list is itself a list of starting values for the JAGS model, or a function creating (possibly random) initial values. If <code>inits</code> is NULL, JAGS will generate initial values for all the model parameters.
<code>n.thin</code>	Thinning interval.
<code>save_model</code>	Logical. If <code>save_model</code> is TRUE a txt file containing the model code is printed in the current working directory.
<code>prior</code>	A list containing the hyperprior values provided by the user. Each element of this list must be a vector containing the user-provided prior distribution and parameter values and must be named with the name of the corresponding parameter. For example, the hyperprior values for the standard deviation parameter for the effects can be provided using the list <code>prior = list('sigma.prior.e' = c("unif", 0, 10))</code> . For more information about how to provide prior hyper-values for different types of parameters and models see details. If <code>prior</code> is set to 'default', the default values will be used.
<code>center</code>	Logical. If <code>center</code> is TRUE, all covariates in both the effect and cost models will be centred.
<code>...</code>	Additional arguments that can be provided by the user. Examples are the additional arguments that can be provided to the function bcea to summarise the health economic evaluation results.

Details

Depending on the distributions specified for the outcome variables in the arguments `dist_e` and `dist_c` and the type of structural value mechanism specified in the argument `type`, different hurdle models are built and run in the background by the function `hurdle`. These are mixture models defined by two components: the first one is a mass distribution at the spike, while the second is a parametric model applied to the natural range of the relevant variable. Usually, a logistic regression is used to estimate the probability of incurring a "structural" value (e.g. 0 for the costs,

or 1 for the effects); this is then used to weigh the mean of the "non-structural" values estimated in the second component. A simple example can be used to show how hurdle models are specified. Consider a data set comprising a response variable y and a set of centered covariates X_j , for $i = j, \dots, J$. Specifically, for each subject in the trial $i = 1, \dots, n$ we define an indicator variable s_i taking value 1 if the i -th individual is associated with a structural value and 0 otherwise. This is modelled as:

$$s_i \sim \text{Bernoulli}(\pi_i)$$

$$\text{logit}(\pi_i) = \sum \gamma_j X_j$$

where

- π_i is the individual probability of a structural value in y .
- γ_j represents the impact on the probability of a structural value in y of the covariate X_j .

When $\gamma_j = 0$, the model assumes a 'SCAR' mechanism, while when $\gamma_j \neq 0$ the mechanism is 'SAR'. For the parameters indexing the structural value model, the default prior distributions assumed are:

- $\gamma_j \sim \text{Normal}(0, 0.01)$

When user-defined hyperprior values are supplied via the argument `prior` in the function `hurdle`, the elements of this list (see Arguments) must be vectors containing the user-provided distribution name and hyperprior values and must take specific names according to the parameters they are associated with. Specifically, the names accepted by **missingHE** are the following:

- auxiliary parameters σ : "sigma.prior.e"(effects) and/or "sigma.prior.c"(costs)
- covariate parameters α_j, β_j : "alpha.prior"(effects) and/or "beta.prior"(costs)
- covariate parameters in the model of the structural values γ_j (if covariate data provided): "gamma.prior.e"(effects) and/or "gamma.prior.c"(costs)

For simplicity, here we assumed that the set of covariates X_j used in the models for the effects/costs and in the model of the structural effect/cost values is the same. However, it is possible to specify different sets of covariates for each model using the arguments in the function `hurdle` (see Arguments).

For each model, random effects can also be specified for each parameter by adding the term $+(x | z)$ to each model formula, where x is the fixed regression coefficient for which also the random effects are desired and z is the clustering variable across which the random effects are specified (must be the name of a factor variable in the dataset). Multiple random effects can be specified using the notation $+(x1 + x2 | \text{site})$ for each covariate that was included in the fixed effects formula.

Value

An object of the class 'missingHE' containing the following elements

- data_set** A list containing the original data set provided in `data` (see Arguments). Additional information is also included about, among others, the number of observed and missing individuals, the total number of individuals by treatment arm and the indicator vectors for the structural values
- model_output** A list containing the output of a JAGS model generated from the functions `jags`, and the posterior samples for the main parameters of the model

cea A list containing the output of the economic evaluation performed using the function [bcea](#)

type A character variable that indicate which type of structural value mechanism used to run the model, either SCAR or SAR (see details)

data_format A character variable that indicates which type of analysis was conducted, either using a wide or long dataset

Author(s)

Andrea Gabrio

References

- Ntzoufras I. (2009). *Bayesian Modelling Using WinBUGS*, John Wiley and Sons.
- Daniels, MJ. Hogan, JW. (2008). *Missing Data in Longitudinal Studies: strategies for Bayesian modelling and sensitivity analysis*, CRC/Chapman Hall.
- Baio, G.(2012). *Bayesian Methods in Health Economics*. CRC/Chapman Hall, London.
- Gelman, A. Carlin, JB., Stern, HS. Rubin, DB.(2003). *Bayesian Data Analysis, 2nd edition*, CRC Press.
- Plummer, M. *JAGS: A program for analysis of Bayesian graphical models using Gibbs sampling*. (2003).

See Also

[jags](#), [bcea](#)

Examples

```
# Quick example to run using the MenSS dataset

# Run the model using the hurdle function assuming a SCAR mechanism
# Use subset of dataset to produce quick results
MenSS_ex <- MenSS[MenSS$age > 25, ]

# Use only 50 iterations to run a quick check
model.hurdle <- hurdle(data = MenSS_ex, model.eff = e ~ trt, model.cost = c ~ trt,
  model.se = se ~ 1, model.sc = sc ~ 1, se = NULL, sc = 0, dist_e = "norm", dist_c = "gamma",
  type = "SCAR", n.chains = 2, n.iter = 50)

# Print the results of the JAGS model
print(model.hurdle)
#

# Use dic information criterion to assess model fit
pic.dic <- pic(model.hurdle, criterion = "dic", cases = "cc")
pic.dic
#

# Extract regression coefficient estimates
coef(model.hurdle)
```

```

#

# Assess model convergence using graphical tools
# Produce histograms of the posterior samples for the mean effects
diag.hist <- diagnostic(model.hurdle, type = "histogram", param = "mu.e")
#

# Compare observed effect data with imputations from the model
# using plots (posterior means and credible intervals)
p1 <- plot(model.hurdle, class = "scatter", outcome = "effects")
#

# Summarise the CEA information from the model
summary(model.hurdle)

# Further examples which take longer to run
model.hurdle <- hurdle(data = MenSS, model.eff = e ~ trt, model.cost = c ~ trt + e,
  model.se = se ~ age, model.sc = sc ~ age, se = 1, sc = 0, dist_e = "beta", dist_c = "gamma",
  type = "SAR", n.chains = 2, n.iter = 500)
#
# Print results for all imputed values
print(model.hurdle)

# Use looic to assess model fit
pic.looic <- pic(model.hurdle, criterion = "looic", cases = "cc")
pic.looic

# Show density plots for mean costs parameters
diag.den <- diagnostic(model.hurdle, type = "denplot", param = "mu.c")

# Plots of imputations for all data
p1 <- plot(model.hurdle, class = "scatter", outcome = "both")

# Summarise the CEA results
summary(model.hurdle)

#
#

```

lmdm

*Full Bayesian Models to handle missingness in Economic Evaluations
(Longitudinal Missing Data Models)*

Description

Full Bayesian cost-effectiveness models to handle missing data in longitudinal outcomes under different missing data mechanism assumptions, using alternative parametric distributions for the

effect and cost variables. The analysis is performed using the BUGS language, which is implemented in the software JAGS using the function `jags`. The output is stored in an object of class 'missingHE'.

Usage

```
lmdm(
  data,
  model.eff,
  model.cost,
  model.me = me ~ 1,
  model.mc = mc ~ 1,
  dist_e,
  dist_c,
  type,
  time_dep = "AR1",
  prob = c(0.025, 0.975),
  n.chains = 2,
  n.iter = 10000,
  n.burnin = floor(n.iter/2),
  inits = NULL,
  n.thin = 1,
  save_model = FALSE,
  prior = "default",
  center = FALSE,
  ...
)
```

Arguments

<code>data</code>	A data frame in which to find the longitudinal variables supplied in <code>model.eff</code> , <code>model.cost</code> (model formulas for effects and costs) and <code>model.me</code> , <code>model.mc</code> (model formulas for the missing effect and cost models). Among these, effectiveness, cost, time and treatment indicator (only two arms) variables must always be provided and named 'e', 'c', 'time' and 'trt', respectively.
<code>model.eff</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic effectiveness outcome ('e') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.cost</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic cost outcome ('c') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. A joint bivariate distribution for effects and costs can be specified by including 'e' on the

	right-hand side of the formula for the costs model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.me</code>	A formula expression in conventional R linear modelling syntax. The response must be indicated with the term 'me' (missing effects) and any covariates must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "probability" parameter for the missing effects through a logistic-linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.mc</code>	A formula expression in conventional R linear modelling syntax. The response must be indicated with the term 'mc' (missing costs) and any covariates must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "probability" parameter for the missing costs through a logistic-linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>dist_e</code>	Distribution assumed for the effects. Current available choices are: Normal ('norm'), Beta ('beta'), Gamma ('gamma'), Exponential ('exp'), Weibull ('weib'), Logistic ('logis'), Poisson ('pois'), Negative Binomial ('negbin') or Bernoulli ('bern').
<code>dist_c</code>	Distribution assumed for the costs. Current available choices are: Normal ('norm'), Gamma ('gamma') or LogNormal ('lnorm').
<code>type</code>	Type of missingness mechanism assumed. Choices are Missing At Random (MAR) and Missing Not At Random (MNAR).
<code>time_dep</code>	Type of dependence structure assumed between effectiveness and cost outcomes. Current choices include: autoregressive structure of order one ('AR1') - default, bivariate at each time ('biv') and independence ('none').
<code>prob</code>	A numeric vector of probabilities within the range (0, 1), representing the upper and lower CI sample quantiles to be calculated and returned for the imputed values.
<code>n.chains</code>	Number of chains.
<code>n.iter</code>	Number of iterations.
<code>n.burnin</code>	Number of warmup iterations.
<code>inits</code>	A list with elements equal to the number of chains selected; each element of the list is itself a list of starting values for the JAGS model, or a function creating (possibly random) initial values. If <code>inits</code> is NULL, JAGS will generate initial values for all the model parameters.
<code>n.thin</code>	Thinning interval.
<code>save_model</code>	Logical. If <code>save_model</code> is TRUE, a txt file containing the model code is printed in the current working directory.
<code>prior</code>	A list containing the hyperprior values provided by the user. Each element of this list must be a vector containing the user-provided prior distribution and parameter values and must be named with the name of the corresponding parameter. For example, the hyperprior values for the standard deviation parameter

	for the effects can be provided using the list <code>prior = list('sigma.prior.e' = c("unif", 0, 10))</code> . For more information about how to provide prior hyper-values for different types of parameters and models see details. If <code>prior</code> is set to 'default', the default values will be used.
center	Logical. If center is TRUE, all covariates in both the effect and cost models will be centred.
...	Additional arguments that can be provided by the user. Examples are the additional arguments that can be provided to the function <code>bcea</code> to summarise the health economic evaluation results.

Details

Depending on the distributions specified for the outcome variables in the arguments `dist_e` and `dist_c` and the type of missingness mechanism specified in the argument `type`, different models are built and run in the background by the function `lmdm`. These models fit multinomial logistic regressions to estimate the probability of a given missing data pattern k ($1 = \text{completers}$, $2 = \text{intermittent}$, $3 = \text{dropout}$) in one or both longitudinal outcomes. A simple example can be used to show how longitudinal missing data models are specified. Consider a longitudinal data set comprising a response variable y measured at S occasions and a set of centered covariate X_j , for $i = j, \dots, J$. For each subject in the trial $i = 1, \dots, n$ and time $s = 1, \dots, S$ we define an indicator variable m_i taking value $k = 1$ if the i -th individual is associated with no missing value (completer), a value $k = 2$ for intermittent missingness over the study period, and a value $k = 3$ for dropout. This is modelled as:

$$m_i \sim \text{Multinomial}(\pi_i^k)$$

$$\pi_i^k = \phi_i^k / \sum \phi_i^k$$

$$\log(\phi_i^k) = \sum \gamma_j^k X_j + \delta^k y_i$$

where

- π_i^k is the individual probability of a missing value in y for pattern k at a given time.
- γ_j^k represents the impact on the missing data probability in y of the covariate X_j for pattern k at a given time.
- δ^k represents the impact on the missing data probability in y for pattern k of missingness itself at a given time.

When $\delta = 0$ the model assumes a 'MAR' mechanism, while when $\delta \neq 0$ the mechanism is 'MNAR'. For the parameters indexing the missingness model, the default prior distributions assumed are:

- $\gamma_j^k \sim \text{Normal}(0, 0.01)$
- $\delta^k \sim \text{Normal}(0, 1)$

When user-defined hyperprior values are supplied via the argument `prior` in the function `lmdm`, the elements of this list (see Arguments) must be vectors containing the user-provided distribution name and hyperprior values and must take specific names according to the parameters they are associated with. Specifically, the names for the parameters indexing the model which are accepted by **missingHE** are the following:

- auxiliary parameters σ : "sigma.prior.e"(effects) and/or "sigma.prior.c"(costs)
- covariate parameters α_j and β_j : "alpha.prior"(effects) and/or "beta.prior"(costs)
- covariate parameters in the missingness model γ_j (if covariate data provided): "gamma.prior.e"(effects) and/or "gamma.prior.c"(costs)
- mnar parameter δ : "delta.prior.e"(effects) and/or "delta.prior.c"(costs)

For simplicity, here we have assumed that the set of covariates X_j used in the models for the effects/costs and in the model of the missing effect/cost values is the same. However, it is possible to specify different sets of covariates for each model using the arguments in the function `lmdm` (see Arguments).

For each model, random effects can also be specified for each parameter by adding the term $+(x | z)$ to each model formula, where x is the fixed regression coefficient for which also the random effects are desired and z is the clustering variable across which the random effects are specified (must be the name of a factor variable in the dataset).

Value

An object of the class 'missingHE' containing the following elements

- data_set** A list containing the original data set provided in `data` (see Arguments). Additional information is also included about, among others, the number of observed and missing individuals, the total number of individuals by treatment arm and the indicator vectors for the missing values
- model_output** A list containing the output of a JAGS model generated from the functions `jags`, and the posterior samples for the main parameters of the model
- cea** A list containing the output of the economic evaluation performed using the function `bcea`
- type** A character variable that indicate which type of missing value mechanism used to run the model, either MAR or MNAR (see details)
- data_format** A character variable that indicates which type of analysis was conducted, either using a wide or long dataset
- time_dep** A character variable that indicate which type of time dependence assumption was made, either none or AR1

Author(s)

Andrea Gabrio

References

- Mason, AJ. Gomes, M. Carpenter, J. Grieve, R. (2021). *Flexible Bayesian longitudinal models for cost-effectiveness analyses with informative missing data*. *Health economics*, 30(12), 3138-3158.
- Daniels, MJ. Hogan, JW. *Missing Data in Longitudinal Studies: strategies for Bayesian modelling and sensitivity analysis*, CRC/Chapman Hall.
- Baio, G.(2012). *Bayesian Methods in Health Economics*. CRC/Chapman Hall, London.
- Gelman, A. Carlin, JB., Stern, HS. Rubin, DB.(2003). *Bayesian Data Analysis, 2nd edition*, CRC Press.
- Plummer, M. *JAGS: A program for analysis of Bayesian graphical models using Gibbs sampling*. (2003).

See Also

[jags](#), [bcea](#)

Examples

```
# Quick example to run using subset of PBS dataset

# Load longitudinal dataset

PBS.long <- PBS

# Run the model using the long_miss function assuming a MAR mechanism
# Use only 100 iterations to run a quick check
model.long <- lmdm(data = PBS.long, model.eff = e ~ trt, model.cost = c ~ trt,
  model.me = me ~ 1, model.mc = mc ~ 1, dist_e = "norm", dist_c = "norm",
  type = "MAR", n.chains = 2, n.iter = 100, time_dep = "none")

# Extract regression coefficient estimates
coef(model.long)
#

# Summarise the CEA information from the model
summary(model.long)

# Further examples which take longer to run
model.long <- lmdm(data = PBS.long, model.eff = e ~ trt, model.cost = c ~ trt + age,
  model.me = me ~ 1, model.mc = mc ~ 1, dist_e = "norm", dist_c = "norm",
  type = "MAR", n.chains = 2, n.iter = 500, time_dep = "none")

# Use looic to assess model fit
pic.looic <- pic(model.long, criterion = "looic")
pic.looic

# Show density plots for all parameters
diag.den <- diagnostic(model.long, type = "denplot", param = "alpha")

# Plots of imputations for all effect data
p1 <- plot(model.long, class = "scatter", outcome = "effects", time.plot = "all")

# Summarise the CEA results
summary(model.long)

#
#
```

Description

Data from a pilot RCT trial (The MenSS trial) on young men at risk of Sexually Transmitted Infections (STIs). A total of 159 individuals were enrolled in trial: 75 in the control (t=1) and 84 in the active intervention (t=2). Clinical and health economic outcome data were collected via self-reported questionnaires at four time points throughout the study: baseline, 3 months, 6 months and 12 months follow-up. Health economic data include utility scores related to quality of life and costs, from which QALYs and total costs were then computed using the area under the curve method and by summing up the cost components at each time point. Clinical data include the total number of instances of unprotected sex and whether the individual was associated with an STI diagnosis or not. Baseline data are available for the utilities (no baseline costs collected), instances of unprotected sex, sti diagnosis, age, ethnicity and employment variables.

Data from a pilot RCT trial (The MenSS trial) on young men at risk of Sexually Transmitted Infections (STIs). A total of 159 individuals were enrolled in trial: 75 in the control (t=1) and 84 in the active intervention (t=2). Clinical and health economic outcome data were collected via self-reported questionnaires at four time points throughout the study: baseline, 3 months, 6 months and 12 months follow-up. Health economic data include utility scores related to quality of life and costs, from which QALYs and total costs were then computed using the area under the curve method and by summing up the cost components at each time point. Clinical data include the total number of instances of unprotected sex and whether the individual was associated with an STI diagnosis or not. Baseline data are available for the utilities (no baseline costs collected), instances of unprotected sex, sti diagnosis, age, ethnicity and employment variables.

Usage

```
data(MenSS)
```

```
data(MenSS)
```

Format

A data frame with 159 rows and 12 variables

A data frame with 159 rows and 12 variables

Details

id id number

e Quality Adjusted Life Years (QALYs)

c Total costs in pounds

u.0 baseline utilities

age Age in years

ethnicity binary: white (1) and other (0)

employment binary: working (1) and other (0)

t Treatment arm indicator for the control (t=1) and the active intervention (t=2)

sex_inst.0 baseline number of instances of unprotected sex

sex_inst number of instances of unprotected sex at 12 months follow-up

sti.0 binary : baseline sti diagnosis (1) and no baseline sti diagnosis (0)
sti binary : sti diagnosis (1) and no sti diagnosis (0) at 12 months follow-up
site site number

id id number
e Quality Adjusted Life Years (QALYs)
c Total costs in pounds
u.0 baseline utilities
age Age in years
ethnicity binary: white (1) and other (0)
employment binary: working (1) and other (0)
trt Treatment arm indicator for the control (t=1) and the active intervention (t=2)
sex_inst.0 baseline number of instances of unprotected sex
sex_inst number of instances of unprotected sex at 12 months follow-up
sti.0 binary : baseline sti diagnosis (1) and no baseline sti diagnosis (0)
sti binary : sti diagnosis (1) and no sti diagnosis (0) at 12 months follow-up
site site number

References

Bailey et al. (2016) Health Technology Assessment 20 ([PubMed](#))

Examples

```
MenSS <- data(MenSS)
summary(MenSS)
str(MenSS)
MenSS <- data(MenSS)
summary(MenSS)
str(MenSS)
```

pattern	<i>Full Bayesian Models to handle missingness in Economic Evaluations (Pattern Mixture Models)</i>
---------	--

Description

Full Bayesian cost-effectiveness models to handle missing data in the outcomes under different missing data mechanism assumptions, using alternative parametric distributions for the effect and cost variables and using a pattern mixture model approach to identify the model. The analysis is performed using the BUGS language, which is implemented in the software JAGS using the function [jags](#) The output is stored in an object of class 'missingHE'.

Usage

```

pattern(
  data,
  model.eff,
  model.cost,
  dist_e,
  dist_c,
  type,
  restriction = "CC",
  prob = c(0.025, 0.975),
  n.chains = 2,
  n.iter = 10000,
  n.burnin = floor(n.iter/2),
  inits = NULL,
  n.thin = 1,
  save_model = FALSE,
  prior = "default",
  center = FALSE,
  ...
)

```

Arguments

<code>data</code>	A data frame in which to find the variables supplied in <code>model.eff</code> , <code>model.cost</code> (model formulas for effects and costs). Among these, effectiveness, cost and treatment indicator (only two arms) variables must always be provided and named 'e', 'c' and 'trt', respectively.
<code>model.eff</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic effectiveness outcome ('e') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.cost</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic cost outcome ('c') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. A joint bivariate distribution for effects and costs can be specified by including 'e' on the right-hand side of the formula for the costs model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>dist_e</code>	Distribution assumed for the effects. Current available choices are: Normal ('norm'), Beta ('beta'), Gamma ('gamma'), Exponential ('exp'), Weibull ('weib'), Logistic ('logis'), Poisson ('pois'), Negative Binomial ('negbin') or Bernoulli ('bern').

<code>dist_c</code>	Distribution assumed for the costs. Current available choices are: Normal ('norm'), Gamma ('gamma') or LogNormal ('lnorm').
<code>type</code>	Type of missingness mechanism assumed. Choices are Missing At Random (MAR) and Missing Not At Random (MNAR).
<code>restriction</code>	type of identifying restriction to be imposed to identify the distributions of the missing data in each pattern. Available choices are: complete case restriction ('CC') - default - or available case restriction ('AC').
<code>prob</code>	A numeric vector of probabilities within the range (0, 1), representing the upper and lower CI sample quantiles to be calculated and returned for the imputed values.
<code>n.chains</code>	Number of chains.
<code>n.iter</code>	Number of iterations.
<code>n.burnin</code>	Number of warmup iterations.
<code>inits</code>	A list with elements equal to the number of chains selected; each element of the list is itself a list of starting values for the JAGS model, or a function creating (possibly random) initial values. If <code>inits</code> is NULL, JAGS will generate initial values for all the model parameters.
<code>n.thin</code>	Thinning interval.
<code>save_model</code>	Logical. If <code>save_model</code> is TRUE, a txt file containing the model code is printed in the current working directory.
<code>prior</code>	A list containing the hyperprior values provided by the user. Each element of this list must be a vector containing the user-provided prior distribution and parameter values and must be named with the name of the corresponding parameter. For example, the hyperprior values for the standard deviation parameter for the effects can be provided using the list <code>prior = list('sigma.prior.e' = c("unif", 0, 10))</code> . For more information about how to provide prior hyper-values for different types of parameters and models see details. If <code>prior</code> is set to 'default', the default values will be used.
<code>center</code>	Logical. If <code>center</code> is TRUE, all covariates in both the effect and cost models will be centred.
<code>...</code>	Additional arguments that can be provided by the user. Examples are the additional arguments that can be provided to the function bcea to summarise the health economic evaluation results.

Details

Depending on the distributions specified for the outcome variables in the arguments `dist_e` and `dist_c` and the type of missingness mechanism specified in the argument `type`, different pattern mixture models are built and run in the background by the function `pattern`. The model for the outcomes is fitted in each missingness pattern and the parameters indexing the missing data distributions are identified using: the corresponding parameters identified from the observed data in other patterns (under 'MAR'); or a combination of the parameters identified by the observed data and some sensitivity parameters (under 'MNAR'). A simple example can be used to show how pattern mixture models are specified. Consider a data set comprising a response variable y and a set of centered covariates X_j . We denote with d_i the patterns' indicator variable for each subject in the

trial $i = 1, \dots, n$ such that: $d_i = 1$ indicates the completers (both e and c observed), $d_i = 2$ and $d_i = 3$ indicate that only the costs or effects are observed, respectively, while $d_i = 4$ indicates that neither of the two outcomes is observed. d_i is assigned a multinomial distribution, which probabilities are modelled using a Dirichlet prior. Next, the outcomes model is fitted in each pattern and parameters that cannot be identified in each pattern ($d = 2, 3, 4$), e.g. $\mu_e[d]$ and $\mu_c[d]$, are identified using some restrictions based on the parameters estimated from other patterns. Two choices are currently available: the complete cases ('CC') or available cases ('AC'). For example, using the 'CC' restriction, the parameters indexing the distributions of the missing data are identified as:

$$\mu_e[2] = \mu_e[4] = \mu_e[1] + \delta_e$$

$$\mu_c[3] = \mu_c[4] = \mu_c[1] + \delta_c$$

where

- $\mu_e[1]$ is the effects mean for the completers.
- $\mu_c[1]$ is the costs mean for the completers.
- δ_e is the sensitivity parameters associated with the marginal effects mean.
- δ_c is the sensitivity parameters associated with the marginal costs mean.

If the 'AC' restriction is chosen, only the parameters estimated from the observed data in pattern 2 (costs) and pattern 3 (effects) are used to identify those in the other patterns. When $\delta_e = 0$ and $\delta_c = 0$ the model assumes a 'MAR' mechanism. When $\delta_e \neq 0$ and/or $\delta_c \neq 0$ 'MNAR' departures for the effects and/or costs are explored with priors on sensitivity parameters that must be provided by the user (see Arguments).

When user-defined hyperprior values are supplied via the argument `prior` in the function `pattern`, the elements of this list (see Arguments) must be vectors containing the user-provided distribution name and hyperprior values and must take specific names according to the parameters they are associated with. Specifically, the names for the parameters indexing the model which are accepted by **missingHE** are the following:

- auxiliary parameters σ : "sigma.prior.e"(effects) and/or "sigma.prior.c"(costs)
- covariate parameters α_j and β_j : "alpha.prior"(effects) and/or "beta.prior"(costs)
- covariate parameters in the missingness model γ_j (if covariate data provided): "gamma.prior.e"(effects) and/or "gamma.prior.c"(costs)
- sensitivity parameters δ : "delta.prior.e"(effects) and/or "delta.prior.c"(costs)
- missingness patterns' probabilities π : "patterns.prior"

For each outcome model, random effects can also be specified for each parameter by adding the term $+(x \mid z)$ to each model formula, where x is the fixed regression coefficient for which also the random effects are desired and z is the clustering variable across which the random effects are specified (must be the name of a factor variable in the dataset). Multiple random effects can be specified using the notation $+(x1 + x2 \mid \text{site})$ for each covariate that was included in the fixed effects formula.

Value

An object of the class 'missingHE' containing the following elements

data_set A list containing the original data set provided in data (see Arguments). Additional information is also included about, among others, the number of observed and missing individuals, the total number of individuals by treatment arm and the indicator vectors for the missing values

model_output A list containing the output of a JAGS model generated from the functions [jags](#), and the posterior samples for the main parameters of the model

cea A list containing the output of the economic evaluation performed using the function [bcea](#)

type A character variable that indicate which type of missing value mechanism used to run the model, either MAR or MNAR (see details)

data_format A character variable that indicates which type of analysis was conducted, either using a wide or long dataset

Author(s)

Andrea Gabrio

References

Daniels, MJ. Hogan, JW. *Missing Data in Longitudinal Studies: strategies for Bayesian modelling and sensitivity analysis*, CRC/Chapman Hall.

Baio, G.(2012). *Bayesian Methods in Health Economics*. CRC/Chapman Hall, London.

Gelman, A. Carlin, JB., Stern, HS. Rubin, DB.(2003). *Bayesian Data Analysis, 2nd edition*, CRC Press.

Plummer, M. *JAGS: A program for analysis of Bayesian graphical models using Gibbs sampling*. (2003).

See Also

[jags](#), [bcea](#)

Examples

```
# Quick example to run using subset of MenSS dataset
MenSS.subset <- MenSS[50:100, ]

# Run the model using the pattern function assuming a MAR mechanism
# Use only 100 iterations to run a quick check
model.pattern <- pattern(data = MenSS.subset,model.eff = e ~ trt, model.cost = c ~ trt,
  dist_e = "norm", dist_c = "norm", type = "MAR", n.chains = 2, n.iter = 100)

# Print the results of the JAGS model
print(model.pattern)
#

# Use dic information criterion to assess model fit
```

```

pic.dic <- pic(model.pattern, criterion = "dic", cases = "cc")
pic.dic
#

# Extract regression coefficient estimates
coef(model.pattern)
#

# Assess model convergence using graphical tools
# Produce histograms of the posterior samples for the mean effects
diag.hist <- diagnostic(model.pattern, type = "histogram", param = "mu.e")
#

# Compare observed effect data with imputations from the model
# using plots (posterior means and credible intervals)
p1 <- plot(model.pattern, class = "scatter", outcome = "effects")
#

# Summarise the CEA information from the model
summary(model.pattern)

# Further examples which take longer to run
model.pattern <- pattern(data = MenSS, model.eff = e ~ trt, model.cost = c ~ trt + e,
  dist_e = "norm", dist_c = "norm", type = "MAR", n.chains = 2, n.iter = 500)
#
# Print results for all imputed values
print(model.pattern)

# Use looic to assess model fit
pic.looic <- pic(model.pattern, criterion = "looic", cases = "cc")
pic.looic

# Show density plots for mean costs parameters
diag.den <- diagnostic(model.pattern, type = "denplot", param = "mu.c")

# Plots of imputations for all data
p1 <- plot(model.pattern, class = "scatter", outcome = "both")

# Summarise the CEA results
summary(model.pattern)

#
#

```

Description

Longitudinal data from a cluster RCT trial (The PBS trial) on people suffering from intellectual disability and challenging behaviour. A total of 244 individuals across 23 sites were enrolled in the trial: 136 in the control (t=1) and 108 in the active intervention (t=2). Health economic outcome data were collected via self-reported questionnaires at three time points throughout the study: baseline (time=1), 6 months (time=2) and 12 months (time=3) follow-up, and included utility scores related to quality of life and costs. Baseline data are available for age, gender, ethnicity, living status, type of carer, marital status, and disability level variables.

Usage

```
data(PBS)
```

Format

A data frame with 732 rows and 16 variables

Details

id id number
time time indicator
e HRQoL utilities
c costs (in pounds)
trt Treatment arm indicator for the control (t=1) and the active intervention (t=2)
age age in years
gender binary: male (1) and female (0)
ethnicity binary: white (1) and other (0)
carer binary: paid carer (1) and family carer (0)
marital binary: single (1) and married (0)
living categorical: alone (1), with partner (2) and with parents (3)
disability categorical: mild (1), moderate (2) and severe (3)
site site number

References

Hassiotis et al. (2014) BMC Psychiatry 14 ([PubMed](#))

Examples

```
PBS <- data(PBS)
summary(PBS)
str(PBS)
```

pic	<i>Predictive information criteria for Bayesian models fitted in JAGS using the function selection, pattern, hurdle or lmdm</i>
-----	---

Description

Efficient approximate leave-one-out cross validation (LOO), deviance information criterion (DIC) and widely applicable information criterion (WAIC) for Bayesian models, calculated on the observed data.

Usage

```
pic(x, criterion = "dic", cases = "cc", ...)
```

Arguments

x	A <code>missingHE</code> object containing the results of a Bayesian model fitted in cost-effectiveness analysis using the function selection , pattern , hurdle or lmdm .
criterion	type of information criteria to be produced. Available choices are 'dic' for the Deviance Information Criterion, 'waic' for the Widely Applicable Information Criterion, and 'looic' for the Leave-One-Out Information Criterion.
cases	group of cases for which information criteria should be computed for: either 'all' for all cases, 'cc' for complete cases, 'ac_e' and 'ac_c' for only the observed effect and cost cases, respectively.
...	Additional parameters that can be provided to manage the output of <code>pic</code> when 'looic' is selected. For more details see bayesplot .

Details

The Deviance Information Criterion (DIC), Leave-One-Out Information Criterion (LOOIC) and the Widely Applicable Information Criterion (WAIC) are methods for estimating out-of-sample predictive accuracy from a Bayesian model using the log-likelihood evaluated at the posterior simulations of the parameters. DIC is computationally simple to calculate but it is known to have some problems, arising in part from it not being fully Bayesian in that it is based on a point estimate. LOOIC can be computationally expensive but can be easily approximated using importance weights that are smoothed by fitting a generalised Pareto distribution to the upper tail of the distribution of the importance weights. WAIC is fully Bayesian and closely approximates Bayesian cross-validation. Unlike DIC, WAIC is invariant to parameterisation and also works for singular models. In finite cases, WAIC and LOOIC give similar estimates, but for influential observations WAIC underestimates the effect of leaving out one observation.

Value

A named list containing different predictive information criteria results and quantities according to the value of `criterion`. In all cases, the measures are computed on the observed data for the specific modules of the model selected in `module`.

- d_bar** Posterior mean deviance (only if criterion is 'dic').
- pD** Effective number of parameters calculated with the formula used by JAGS (only if criterion is 'dic').
- dic** Deviance Information Criterion calculated with the formula used by JAGS (only if criterion is 'dic').
- d_hat** Deviance evaluated at the posterior mean of the parameters and calculated with the formula used by JAGS (only if criterion is 'dic').
- elpd, elpd_se** Expected log pointwise predictive density and standard error calculated on the observed data for the model nodes indicated in module (only if criterion is 'waic' or 'looic').
- p, p_se** Effective number of parameters and standard error calculated on the cases indicated in cases. (only if criterion is 'waic' or 'looic').
- looic, looic_se** The leave-one-out information criterion and standard error calculated on the cases indicated in cases. (only if criterion is 'looic').
- waic, waic_se** The widely applicable information criterion and standard error calculated on the cases indicated in cases. (only if criterion is 'waic').
- pointwise** A matrix containing the pointwise contributions of each of the above measures calculated on the cases indicated in cases. (only if criterion is 'waic' or 'looic').
- diagnostics** A named list containing additional diagnostic measures (only if criterion is 'looic'). See [loo](#) for details about interpreting the list elements.
- psis_object** A named list containing the matrix of (smoothed) log weights (only if criterion is 'looic' with the optional argument 'save_psis' is set to TRUE). See [loo](#) for details about interpreting the list elements.'

Author(s)

Andrea Gabrio

References

- Plummer, M. *JAGS: A program for analysis of Bayesian graphical models using Gibbs sampling*. (2003).
- Vehtari, A. Gelman, A. Gabry, J. (2016a) Practical Bayesian model evaluation using leave-one-out cross-validation and WAIC. *Statistics and Computing*. Advance online publication.
- Vehtari, A. Gelman, A. Gabry, J. (2016b) Pareto smoothed importance sampling. *ArXiv* preprint.
- Gelman, A. Hwang, J. Vehtari, A. (2014) Understanding predictive information criteria for Bayesian models. *Statistics and Computing* 24, 997-1016.
- Watanable, S. (2010). Asymptotic equivalence of Bayes cross validation and widely application information criterion in singular learning theory. *Journal of Machine Learning Research* 11, 3571-3594.

See Also

[jags](#), [loo](#), [waic](#)

Examples

```
# For examples see the function \code{\link{selection}}, \code{\link{pattern}},
# \code{\link{hurdle}} or \code{\link{lmdm}}
#
#
```

plot.missingHE	<i>Plot method for the imputed data contained in the objects of class missingHE</i>
----------------	---

Description

Produces a plot of the observed and imputed values (with credible intervals) for the effect and cost outcomes from a Bayesian cost-effectiveness analysis model with two treatment arms, implemented using the function [selection](#), [pattern](#), [hurdle](#) or [lmdm](#). The graphical layout is obtained from the functions contained in the package **ggplot2** and **ggthemes**.

Usage

```
## S3 method for class 'missingHE'
plot(
  x,
  prob = c(0.025, 0.975),
  class = "scatter",
  outcome = "both",
  trt = "all",
  time_plot = NULL,
  theme = NULL,
  only.plot = TRUE,
  ...
)
```

Arguments

x	A missingHE object containing the results of the Bayesian model for cost-effectiveness analysis.
prob	A numeric vector of probabilities representing the upper and lower CI sample quantiles to be calculated and returned for the imputed values.
class	Type of the plot comparing the observed and imputed outcome data. Available choices are 'scatter' (default), 'histogram' and 'boxplot' for a scatter, histogram or a boxplot of the observed and average imputed outcome data, respectively.
outcome	The outcome variables that should be displayed. Options are: 'both' (default) for both effects and costs; 'effects' or 'costs' for the effects or costs separately.
trt	treatment group for which plots should be displayed. Choices include: 'all' (default) for all groups; 'none' for results across all groups; any character or numeric value denoting the treatment group name or index associated with the treatment variable in the original data set.

time_plot	Time point for which the graphs should be displayed.
theme	Type of ggplot theme among some pre-defined themes, mostly taken from the package ggthemes . For a full list of available themes see details.
only.plot	Logical. If only.plot is TRUE (default) only the plot is returned. When only.plot is FALSE, a list containing the plot object and the data is returned instead.
...	Additional parameters that can be provided to manage the output of plot.missingHE.

Details

The function produces a plot of the observed and imputed effect and cost data in a two-arm based cost-effectiveness model implemented using the function [selection](#), [pattern](#), [hurdle](#) or [lmdm](#). The purpose of this graph is to visually compare the outcome values for the fully-observed individuals with those imputed by the model for the missing individuals. For scatter plots, average imputed values are also associated with credible intervals specified in the argument prob. The argument theme allows to customise the graphical aspect of the plots generated by plot.missingHE and allows to choose among a set of possible pre-defined themes taken from the package **ggtheme**. For a complete list of the available character names for each theme and scheme set, see **ggthemes** and **bayesplot**.

Value

A ggplot object containing the plots specified in the argument class.

Author(s)

Andrea Gabrio

References

- Daniels, MJ. Hogan, JW. (2008) *Missing Data in Longitudinal Studies: strategies for Bayesian modelling and sensitivity analysis*, CRC/Chapman Hall.
- Molenberghs, G. Fitzmaurice, G. Kenward, MG. Tsiatis, A. Verbeke, G. (2015) *Handbook of Missing Data Methodology*, CRC/Chapman Hall.

See Also

[selection](#) [pattern](#) [hurdle](#) [lmdm](#) [diagnostic](#)

Examples

```
# For examples see the function \code{\link{selection}}, \code{\link{pattern}},
# \code{\link{hurdle}} or \code{\link{lmdm}}
#
#
```

postsum	<i>Postsum method for inspecting summary posterior estimates of a Bayesian model fitted in JAGS</i>
---------	---

Description

Prints the summary table for the model fitted, with the estimate of the parameters and/or missing values.

Usage

```
postsum(x, ...)

## S3 method for class 'missingHE'
postsum(x, display = "fixed", digits = 3, ...)
```

Arguments

x	A missingHE object containing the results of the Bayesian model run using the function selection , pattern , hurdle or lmdm .
...	additional arguments affecting the output produced. For example: param = JAGS name assigned to the specific model parameters. to be shown in the printed table.
display	Set of parameters for which posterior summaries are displayed. Choices are: fixed effects ('fixed'), random effects ('random'), individual log likelihood values ('loglik'), individual conditional parameter values ('conditional') and individual imputed values ('mis').
digits	Integer indicating the number of decimal places to be used for rounding (default = 3).

Author(s)

Andrea Gabrio

ppc	<i>Posterior predictive checks for assessing the fit to the observed data of Bayesian models implemented in JAGS using the function selection, pattern, hurdle or lmdm</i>
-----	--

Description

The focus is restricted to full Bayesian models in cost-effectiveness analyses based on the function [selection](#), [pattern](#), [hurdle](#) or [lmdm](#) with the fit to the observed data being assessed through graphical checks based on the posterior replications generated from the model. Examples include the comparison of histograms, density plots, intervals, test statistics, evaluated using both the observed and replicated data. Different types of posterior predictive checks are implemented to assess model fit using functions contained in the package **bayesplot**. Graphics and plots are managed using functions contained in the package **ggplot2** and **ggthemes**.

Usage

```
ppc(
  x,
  type = "histogram",
  outcome = "both",
  ndisplay = 15,
  trt = "all",
  theme = NULL,
  scheme_set = NULL,
  ...
)
```

Arguments

x	An object of class "missingHE" containing the posterior results of a full Bayesian model implemented using the function selection , pattern , hurdle or lmdm .
type	Type of posterior predictive check among some pre-defined types, mostly taken from the package bayesplot . For a full list of available options see details.
outcome	The outcome variables that should be displayed. Options are: 'both' (default) for both effects and costs; 'effects' or 'costs' for the effects or costs separately.
ndisplay	Number of posterior replications to be used to generate the plots.
trt	treatment group for which plots should be displayed. Choices include: 'all' (default) for all groups; 'none' for results across all groups; any character or numeric value denoting the treatment group name or index associated with the treatment variable in the original data set.
theme	Type of ggplot theme among some pre-defined themes, mostly taken from the package ggthemes . For a full list of available themes see details.
scheme_set	Type of scheme sets among some pre-defined schemes, mostly taken from the package bayesplot . For a full list of available themes see details.
...	Additional parameters that can be provided to manage the output of ppc. For more details see bayesplot .

Details

The function produces different types of graphical posterior predictive checks using the estimates from a Bayesian cost-effectiveness model implemented with the function [selection](#), [pattern](#),

[hurdle](#) or [lmdm](#). The purpose of these checks is to visually compare the distribution (or some relevant quantity) of the observed data with respect to that from the replicated data for both effectiveness and cost outcomes in each treatment arm. Since predictive checks are meaningful only with respect to the observed data, only the observed outcome values are used to assess the fit of the model. The arguments `theme` and `scheme_set` allow to customise the graphical aspect of the plots generated by `ppc` and allow to choose among a set of possible pre-defined themes and scheme sets taken from the package **ggtheme** and **bayesplot**. For a complete list of the available character names for each theme and scheme set, see **ggthemes** and **bayesplot**.

Value

A ggplot object containing the plots specified in the argument `type`.

Author(s)

Andrea Gabrio

References

Gelman, A. Carlin, JB., Stern, HS. Rubin, DB.(2003). *Bayesian Data Analysis, 2nd edition*, CRC Press.

See Also

[selection](#) [pattern](#) [hurdle](#) [lmdm](#) [diagnostic](#)

Examples

```
# For examples see the function \code{\link{selection}}, \code{\link{pattern}},
# \code{\link{hurdle}} or \code{\link{lmdm}}
#
```

print.missingHE	<i>Print method for objects in the class missingHE</i>
-----------------	--

Description

Produces a printout of the (posterior mean) estimate for each regression coefficient included in the outcome and missingness/structural value models based on the health economic evaluation probabilistic model run using the function [selection](#), [pattern](#), [hurdle](#) or [lmdm](#).

Usage

```
## S3 method for class 'missingHE'
print(x, digits = 3, ...)
```

Arguments

<code>x</code>	A <code>missingHE</code> object containing the results of the Bayesian modelling and the economic evaluation.
<code>digits</code>	Integer indicating the number of decimal places to be used for rounding (default = 3).
<code>...</code>	Additional arguments affecting the summary produced.

Value

Prints all fixed regression coefficients based on the type of model fitted using the function `selection`, `pattern`, `hurdle` or `lmdm`. Summary estimates based on posterior means of each fixed regression coefficient included into the fitted models are provided.

Author(s)

Andrea Gabrio

References

Baio, G.(2012). *Bayesian Methods in Health Economics*. CRC/Chapman Hall, London.

See Also

[selection](#) [pattern](#) [hurdle](#) [lmdm](#) [diagnostic](#) [plot.missingHE](#)

Examples

```
# For examples see the function \code{\link{selection}}, \code{\link{pattern}},
# \code{\link{hurdle}} or \code{\link{lmdm}}
#
#
```

selection

*Full Bayesian Models to handle missingness in Economic Evaluations
(Selection Models)*

Description

Full Bayesian cost-effectiveness models to handle missing data in the outcomes under different missing data mechanism assumptions, using alternative parametric distributions for the effect and cost variables and using a selection model approach to identify the model. The analysis is performed using the BUGS language, which is implemented in the software JAGS using the function `jags`. The output is stored in an object of class `'missingHE'`.

Usage

```

selection(
  data,
  model.eff,
  model.cost,
  model.me = me ~ 1,
  model.mc = mc ~ 1,
  dist_e,
  dist_c,
  type,
  prob = c(0.025, 0.975),
  n.chains = 2,
  n.iter = 10000,
  n.burnin = floor(n.iter/2),
  inits = NULL,
  n.thin = 1,
  save_model = FALSE,
  prior = "default",
  center = FALSE,
  ...
)

```

Arguments

<code>data</code>	A data frame in which to find the variables supplied in <code>model.eff</code> , <code>model.cost</code> (model formulas for effects and costs) and <code>model.me</code> , <code>model.mc</code> (model formulas for the missing effect and cost models). Among these, effectiveness, cost and treatment indicator (only two arms) variables must always be provided and named 'e', 'c' and 'trt', respectively.
<code>model.eff</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic effectiveness outcome ('e') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.cost</code>	A formula expression in conventional R linear modelling syntax. The response must be a health economic cost outcome ('c') whose name must correspond to that used in <code>data</code> . Any covariates in the model must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "location" parameter of the distribution through a linear model. A joint bivariate distribution for effects and costs can be specified by including 'e' on the right-hand side of the formula for the costs model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.me</code>	A formula expression in conventional R linear modelling syntax. The response must be indicated with the term 'me'(missing effects) and any covariates must

	be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "probability" parameter for the missing effects through a logistic-linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>model.mc</code>	A formula expression in conventional R linear modelling syntax. The response must be indicated with the term 'mc'(missing costs) and any covariates must be provided on the right-hand side of the formula. If there are no covariates, 1 should be specified on the right hand side of the formula. By default, covariates are placed on the "probability" parameter for the missing costs through a logistic-linear model. Random effects can also be specified for each model parameter. See details for how these can be specified.
<code>dist_e</code>	Distribution assumed for the effects. Current available choices are: Normal ('norm'), Beta ('beta'), Gamma ('gamma'), Exponential ('exp'), Weibull ('weib'), Logistic ('logis'), Poisson ('pois'), Negative Binomial ('negbin') or Bernoulli ('bern').
<code>dist_c</code>	Distribution assumed for the costs. Current available choices are: Normal ('norm'), Gamma ('gamma') or LogNormal ('lnorm').
<code>type</code>	Type of missingness mechanism assumed. Choices are Missing At Random (MAR) and Missing Not At Random (MNAR).
<code>prob</code>	A numeric vector of probabilities within the range (0, 1), representing the upper and lower CI sample quantiles to be calculated and returned for the imputed values.
<code>n.chains</code>	Number of chains.
<code>n.iter</code>	Number of iterations.
<code>n.burnin</code>	Number of warmup iterations.
<code>inits</code>	A list with elements equal to the number of chains selected; each element of the list is itself a list of starting values for the JAGS model, or a function creating (possibly random) initial values. If inits is NULL, JAGS will generate initial values for all the model parameters.
<code>n.thin</code>	Thinning interval.
<code>save_model</code>	Logical. If save_model is TRUE, a txt file containing the model code is printed in the current working directory.
<code>prior</code>	A list containing the hyperprior values provided by the user. Each element of this list must be a vector containing the user-provided prior distribution and parameter values and must be named with the name of the corresponding parameter. For example, the hyperprior values for the standard deviation parameter for the effects can be provided using the list <code>prior = list('sigma.prior.e' = c("unif", 0, 10))</code> . For more information about how to provide prior hyper-values for different types of parameters and models see details. If prior is set to 'default', the default values will be used.
<code>center</code>	Logical. If center is TRUE, all covariates in both the effect and cost models will be centred.
<code>...</code>	Additional arguments that can be provided by the user. Examples are the additional arguments that can be provided to the function bcea to summarise the health economic evaluation results.

Details

Depending on the distributions specified for the outcome variables in the arguments `dist_e` and `dist_c` and the type of missingness mechanism specified in the argument `type`, different selection models are built and run in the background by the function `selection`. These models consist in logistic regressions to estimate the probability of missingness in one or both outcomes. A simple example can be used to show how selection models are specified. Consider a data set comprising a response variable y and a set of covariates X_j , for $i = j, \dots, J$. For each subject in the trial $i = 1, \dots, n$ we define an indicator variable m_i taking value 1 if the i -th individual is associated with a missing value and 0 otherwise. This is modelled as:

$$m_i \sim \text{Bernoulli}(\pi_i)$$

$$\text{logit}(\pi_i) = \sum \gamma_j X_j + \delta y_i$$

where

- π_i is the individual probability of a missing value in y .
- γ_j represents the impact on the probability of a missing value in y of the covariate X_j .
- δ represents the impact on the probability of a missing value in y of the outcome values.

When $\delta = 0$ the model assumes a 'MAR' mechanism, while when $\delta \neq 0$ the mechanism is 'MNAR'. For the parameters indexing the missingness model, the default prior distributions assumed are:

- $\gamma_j \sim \text{Normal}(0, 0.01)$
- $\delta \sim \text{Normal}(0, 1)$

When user-defined hyperprior values are supplied via the argument `prior` in the function `selection`, the elements of this list (see Arguments) must be vectors containing the user-provided distribution name and hyperprior values and must take specific names according to the parameters they are associated with. Specifically, the names for the parameters indexing the model which are accepted by **missingHE** are the following:

- auxiliary parameters σ : "sigma.prior.e"(effects) and/or "sigma.prior.c"(costs)
- covariate parameters α_j and β_j : "alpha.prior"(effects) and/or "beta.prior"(costs)
- covariate parameters in the missingness model γ_j (if covariate data provided): "gamma.prior.e"(effects) and/or "gamma.prior.c"(costs)
- mnar parameter δ : "delta.prior.e"(effects) and/or "delta.prior.c"(costs)

For simplicity, here we have assumed that the set of covariates X_j used in the models for the effects/costs and in the model of the missing effect/cost values is the same. However, it is possible to specify different sets of covariates for each model using the arguments in the function `selection` (see Arguments).

For each model, random effects can also be specified for each parameter by adding the term $+(x | z)$ to each model formula, where x is the fixed regression coefficient for which also the random effects are desired and z is the clustering variable across which the random effects are specified (must be the name of a factor variable in the dataset). Multiple random effects can be specified using the notation $+(x1 + x2 | \text{site})$ for each covariate that was included in the fixed effects formula.

Value

An object of the class 'missingHE' containing the following elements

data_set A list containing the original data set provided in data (see Arguments). Additional information is also included about, among others, the number of observed and missing individuals, the total number of individuals by treatment arm and the indicator vectors for the missing values

model_output A list containing the output of a JAGS model generated from the functions [jags](#), and the posterior samples for the main parameters of the model

cea A list containing the output of the economic evaluation performed using the function [bcea](#)

type A character variable that indicate which type of missing value mechanism used to run the model, either MAR or MNAR (see details)

data_format A character variable that indicates which type of analysis was conducted, either using a wide or long dataset

Author(s)

Andrea Gabrio

References

Daniels, MJ. Hogan, JW. *Missing Data in Longitudinal Studies: strategies for Bayesian modelling and sensitivity analysis*, CRC/Chapman Hall.

Baio, G.(2012). *Bayesian Methods in Health Economics*. CRC/Chapman Hall, London.

Gelman, A. Carlin, JB., Stern, HS. Rubin, DB.(2003). *Bayesian Data Analysis, 2nd edition*, CRC Press.

Plummer, M. *JAGS: A program for analysis of Bayesian graphical models using Gibbs sampling*. (2003).

See Also

[jags](#), [bcea](#)

Examples

```
# Quick example to run using subset of MenSS dataset
MenSS.subset <- MenSS[50:100, ]

# Run the model using the selection function assuming a SCAR mechanism
# Use only 100 iterations to run a quick check
model.selection <- selection(data = MenSS.subset, model.eff = e ~ trt, model.cost = c ~ trt,
  model.me = me ~ 1, model.mc = mc ~ 1, dist_e = "norm", dist_c = "norm",
  type = "MAR", n.chains = 2, n.iter = 100)

# Print the results of the JAGS model
print(model.selection)
#
```

```

# Use dic information criterion to assess model fit
pic.dic <- pic(model.selection, criterion = "dic", cases = "cc")
pic.dic
#

# Extract regression coefficient estimates
coef(model.selection)
#

# Assess model convergence using graphical tools
# Produce histograms of the posterior samples for the mean effects
diag.hist <- diagnostic(model.selection, type = "histogram", param = "mu.e")
#

# Compare observed effect data with imputations from the model
# using plots (posterior means and credible intervals)
p1 <- plot(model.selection, class = "scatter", outcome = "effects")
#

# Summarise the CEA information from the model
summary(model.selection)

# Further examples which take longer to run
model.selection <- selection(data = MenSS, model.eff = e ~ trt, model.cost = c ~ trt + e,
  model.se = me ~ age, model.mc = mc ~ age, dist_e = "norm", dist_c = "norm",
  type = "MAR", n.chains = 2, n.iter = 500)
#
# Print results for all imputed values
print(model.selection)

# Use looic to assess model fit
pic.looic <- pic(model.selection, criterion = "looic", cases = "cc")
pic.looic

# Show density plots for mean costs parameters
diag.den <- diagnostic(model.selection, type = "denplot", param = "mu.c")

# Plots of imputations for all data
p1 <- plot(model.selection, class = "scatter", outcome = "both")

# Summarise the CEA results
summary(model.selection)

#
#

```

Description

Produces a table printout with some summary results of the health economic evaluation probabilistic model run using the function [selection](#), [pattern](#), [hurdle](#) or [lmdm](#).

Usage

```
## S3 method for class 'missingHE'
summary(object, incremental = FALSE, prob = c(0.025, 0.975), digits = 3, ...)
```

Arguments

object	A missingHE object containing the results of the Bayesian modelling and the economic evaluation
incremental	Logical. If incremental is TRUE, incremental CE results are printed.
prob	A numeric vector of probabilities within the range (0, 1), representing the upper and lower CI quantiles to be calculated and returned for the posterior estimates.
digits	Integer indicating the number of decimal places to be used for rounding (default = 3).
...	Additional arguments affecting the summary produced.

Value

Prints tables with information on the CE results based on a model fitted using the function [selection](#), [pattern](#) or [hurdle](#). Summary information on the main parameters of interests is provided.

Author(s)

Andrea Gabrio

References

Baio, G.(2012). *Bayesian Methods in Health Economics*. CRC/Chapman Hall, London.

See Also

[selection](#) [pattern](#) [hurdle](#) [lmdm](#) [diagnostic](#) [plot.missingHE](#)

Examples

```
# For examples see the function selection, pattern or hurdle
#
#
```

Index

- * **CEA**
 - hurdle, 6
 - lmdm, 11
 - pattern, 18
 - selection, 32
 - * **Hurdle**
 - hurdle, 6
 - * **JAGS**
 - hurdle, 6
 - lmdm, 11
 - pattern, 18
 - pic, 25
 - postsum, 29
 - selection, 32
 - * **MCMC**
 - diagnostic, 3
 - ppc, 29
 - * **Mixture**
 - pattern, 18
 - * **Models**
 - hurdle, 6
 - pattern, 18
 - selection, 32
 - * **Pattern**
 - pattern, 18
 - * **Selection**
 - selection, 32
 - * **checks**
 - diagnostic, 3
 - ppc, 29
 - * **convergence**
 - diagnostic, 3
 - * **datasets**
 - MenSS, 16
 - PBS, 23
 - * **data**
 - hurdle, 6
 - lmdm, 11
 - pattern, 18
 - plot.missingHE, 27
 - postsum, 29
 - selection, 32
 - * **diagnostics**
 - diagnostic, 3
 - * **dic**
 - pic, 25
 - * **longitudinal**
 - lmdm, 11
 - * **loo**
 - pic, 25
 - * **missing**
 - hurdle, 6
 - lmdm, 11
 - pattern, 18
 - plot.missingHE, 27
 - postsum, 29
 - selection, 32
 - * **models**
 - lmdm, 11
 - * **plot**
 - plot.missingHE, 27
 - * **posterior**
 - ppc, 29
 - * **predictive**
 - ppc, 29
 - * **print**
 - postsum, 29
 - * **replications**
 - ppc, 29
 - * **waic**
 - pic, 25
- bcea, 8, 10, 14–16, 20, 22, 34, 36
- coef.missingHE, 2
- diagnostic, 3, 3, 28, 31, 32, 38
- ggs, 6

`hurdle`, [2–4](#), [6](#), [6](#), [25](#), [27–32](#), [38](#)

`jags`, [6](#), [9](#), [10](#), [12](#), [15](#), [16](#), [18](#), [22](#), [26](#), [32](#), [36](#)

`lmdm`, [2–4](#), [6](#), [11](#), [25](#), [27–32](#), [38](#)

`loo`, [26](#)

`MenSS`, [16](#)

`pattern`, [2–4](#), [6](#), [18](#), [25](#), [27–32](#), [38](#)

`PBS`, [23](#)

`pic`, [25](#)

`plot.missingHE`, [3](#), [27](#), [32](#), [38](#)

`postsum`, [29](#)

`ppc`, [29](#)

`print.missingHE`, [31](#)

`selection`, [2–4](#), [6](#), [25](#), [27–32](#), [32](#), [38](#)

`summary.missingHE`, [37](#)

`waic`, [26](#)